


SylCore IP65

SYLCORE 740LM 830 IP65 WHT
0005074



Product features

- Integrated LED recessed spotlight, white bezel colour, white reflector, 740lm, 9.0W, dimmable trailing/leading edge, 3000K, 40° degree beam angle, polycarbonate and aluminium body, low profile 62mm recessed depth, IP65 from the front, IK03, loop-in/loop-out terminals for fast wiring, weight 0,165Kg, 85mm bezel diameter, 68-74mm cutout, clear lens.



PRODUCT OVERVIEW

Product name	SYLCORE 740LM 830 IP65 WHT
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting
General application	Residential & Consumer
ETIM Class	Downlight/spot/floodlight
Warranty	3 years
Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	82
Colour temperature (K)	3000
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Photobiological Risk Group	RG1
Total power consumption (W)	9
Electrical protection	Class II
Dimmable	Yes
Minimum dimming level (%)	10
LED Flickering Rate	Low (6% - 20%)
Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK03
Product EAN number	5410288050744

DATA TABLE

General data

Product name	SYLCORE 740LM 830 IP65 WHT
Technology	LED
Housing	Aluminium
Mount	Ceiling recessed mounting

SylCore IP65

SYLCORE 740LM 830 IP65 WHT
0005074

General application	Residential & Consumer
Operating temperature range (°C)	-10°C - 35°C
Performance ambient temperature Tq (°C)	25
ETIM Class	Downlight/spot/floodlight
Warranty	3 years

Optical data

Fixture luminous flux (lm)	740
Luminaire efficacy (lm/W)	82
Colour temperature (K)	3000
Colour Code	830
Light colour	Warm White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM5
Beam Angle (°)	40
Distribution type	Symmetric
Photobiological Risk Group	RG1

Electrical data

Total power consumption (W)	9
Mains voltage (V)	220-240V~
Electrical protection	Class II
Control gear required	No
Transformer required	No
Dimmable	Yes
Minimum dimming level (%)	10
Drive current (mA)	165
Inrush Current (A)	10
Inrush Duration (µs)	150
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Low (6% - 20%)
Max. Luminaires per 10A C Breaker	50
Max. Luminaires per 13A C Breaker	65
Max. Luminaires per 16A C Breaker	80
Max. Luminaires per 20A C Breaker	100

Lifetime data

Lifespan L70 B50	47000
------------------	-------

Physical data

Housing colour	RAL 9016 - Traffic white / Bezel
IP rating	IP65/20
IK rating	IK03
Nominal Product Length (mm)	86
Nominal Product Width (mm)	86
Nominal Product Height (mm)	64
Nominal Product Diameter (mm)	86

SylCore IP65 SYLCORE 740LM 830 IP65 WHT 0005074

Weight (kg)	0.14
Recessed Depth (mm)	100


Packaging

Single packaging type	Carton
Product EAN number	5410288050744
Packaging single length / height (cm)	10.0
Packaging single width (cm)	10.0
Packaging single depth (cm)	8.5
DUN14 (inner)	25410288050748
Units per inner package	6
Packaging inner length / height (cm)	28.5
Packaging inner width (cm)	9.0
Packaging inner depth (cm)	19.0
DUN14 (outer)	15410288050741
Units per outer package	36
Packaging outer length / height (cm)	43.6
Packaging outer width (cm)	35.6
Packaging outer depth (cm)	29.3

Safety data

Optimal operating condition (°C)	-10-35
----------------------------------	--------

PHOTOMETRY



TECHNICAL DRAWINGS

