

PRODUCT DATASHEET

LED WORKLIGHT VALUE TRIPOD 2x30W 865

WORKLIGHT VALUE TRIPOD | Versatile LED worklight with tripod stand in value class



Areas of application

- Renovation
- Garages
- Workshops
- Basement

Product benefits

- Foldable for easy storage
- Portable worklight for flexible applications

Product features

- Available with 1 or 2 luminaire heads
- Rotation angle luminaire head: 360°, swiveling: 180°
- Type of protection, luminaire head and housing: IP65/IP54, Type of protection, plug: IP44
- Height adjustment of tripod up to 1.8 m total height



TECHNICAL DATA

Electrical data


| | |
|---|-----------------------|
| Nominal wattage | 60.00 W |
| Nominal voltage | 220...240 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 280.000 mA |
| Inrush current | 4.1 A |
| Inrush current time T_{h50} | 0.5 μ s |
| Max. number of luminaires per miniature circuit breaker B16 | 98 |
| Max. number of luminaires per miniature circuit breaker C16 | 98 |
| Power factor λ | ≥ 0.90 |
| Protection class | I |
| Operating mode | Integrated LED driver |

Photometrical data

| | |
|--|---------------|
| Luminous flux | 6000 lm |
| Total luminous flux of contained light sources | 7000 lm |
| Luminous efficacy | 100 lm/W |
| Color temperature | 6500 K |
| Light color (designation) | Cool Daylight |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | < 6 sdcM |
| Luminous intensity | 2200 cd |
| Flickering metric (Pst LM) | <1 |
| Stroboscope effect metric (SVM) | <0.9 |
| Photobiological safety group acc. to EN62778 | RG1 |
| Beam angle | 115 ° |

Dimensions & Weight

| | |
|----------------|------------|
| Length | 1153.00 mm |
| Width | 1000.00 mm |
| Height | 1871.00 mm |
| Product weight | 5150.00 g |



Materials & Colors

| | |
|--|------------|
| Product color | Black/Gray |
| Housing color | Black/Gray |
| Body material | Aluminum |
| Cover material | Glass |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|------------------|
| Ambient temperature range | -20...+40 °C |
| Temperature range at storage | -20...+80 °C |
| Type of connection | Plug type C (EU) |
| Type of protection | IP54 |
| Protection class IK (shock resistance) | IK06 |
| Dimmable | No |
| Mounting type | Standing |
| LED module replaceable | Not replaceable |
| With light source | Yes |

Lifespan

| | |
|----------------------------|-----------------------|
| Lifespan L70/B50 at 25 °C | 30000 h ¹⁾ |
| Number of switching cycles | 15000 |

¹⁾ t[h]: L70 / B50 @ 25 °C (Ta), t[h]: L80 / B10 @ 25 °C (Ta), t[h]: L90 / B10 @ 25 °C (Ta)

Certificates & Standards

| | |
|--|----|
| Standards | CE |
| Luminaire with limited surface temperature, "D sign" | No |

Additional product data




| | |
|----------------|-----------------------------|
| Product remark | Available from October 2023 |
|----------------|-----------------------------|

| | |
|-----------------------|---|
| Number of illuminants | 2 |
|-----------------------|---|

EQUIPMENT / ACCESSORIES

- 1,5m power cable for flexible installation

DOWNLOAD DATA

| Documents and certificates | |
|--|-------------------------------|
|  | User instruction |
|  | Packaging insert |
|  | Declarations Of Conformity CE |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075831414 | Folding box 1 | 195 mm x 240 mm x 820 mm | 5568.00 g | 38.38 dm ³ |
| 4058075831421 | Shipping box 1 | 835 mm x 210 mm x 265 mm | 6300.00 g | 46.47 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.