

PRODUCT DATASHEET HCI-T 35 W/942 NDL PB

POWERBALL HCI®-T | Metal halide lamps with ceramic technology for enclosed luminaires



Areas of application

- Shop interiors, shop windows
- Shopping arcades
- Foyers, reception areas
- Museums, exhibitions
- Exhibition halls and trade fairs
- Factories and workshops
- Approved only for use in enclosed luminaires
- Outdoor applications only in suitable luminaires

Product benefits

- Very high efficiency
- Good to excellent color rendering
- Very good color stability
- UV values significantly below the maximum permitted thresholds to IEC 61167 thanks to UV filter

Product features

- POWERBALL® ceramic technology
- Light colors: warm white (830 WDL, 930 WDL), neutral white (942 NDL)
- Average lifetime: 15,000 h (ECG with 70...400 Hz square-wave current)
- Average lifetime 150 W version: 20,000 h (ECG with 70...400 Hz square-wave current)
- Average lifetime: 12,000 h (with magnetic control gear)



TECHNICAL DATA

Electrical data

Nominal wattage	35 W
Construction wattage	39.00 W
Nominal voltage	86 V
Ignition voltage	3.6/5.0 kVp ¹⁾
Nominal current	0.53 A
PFC capacitor at 50 Hz	6 µF


¹⁾ Minimum / for superimposed ignition with square wave electronic ballast 3.0 kVp are sufficient

Photometrical data

Luminous flux	3400 lm ¹⁾
Luminous efficacy	87 lm/W ²⁾
Color temperature	3750 K
Color rendering index Ra	91
Light color	937
UV protection	Yes

¹⁾ In operation with electronic control gear with 70...400 Hz square-wave current. Operation with magnetic ballast can be less efficient

²⁾ In operation with low frequency square wave electronic ballast, 70...400 Hz. Operation with electromagnetic ballast may be less efficient.



Dimensions & Weight

Overall length	100.00 mm
Light center length (LCL)	56,0 mm
Diameter	20,0 mm
Product weight	27.00 g

Temperatures & operating conditions

Maximum permitted outer bulb temperature	500 °C
Maximum permitted pinch temperature	350 °C

Lifespan

Lifespan B50	15000 h ¹⁾
--------------	-----------------------

¹⁾ At ECG

Additional product data

Base (standard designation)	G12
Mercury content	5.4 mg ¹⁾
Mercury-free	No
Design / version	Clear
System guarantee level	3 (2/5)

¹⁾ Maximum

Capabilities

Dimmable	No
Burning position	Any
Enclosed luminaire required	Yes
Hot restart	No

Certificates & Standards

Energy efficiency class	F
-------------------------	---

Country-specific categorizations

ILCOS	MT/UB-35/942-H/SL-G12-20/90
Order reference	HCI-T 35W/942 N

Energy labelling regulation data acc EU 2019/2015

Light source cap-type (or other electric interface)	G12
Length	100.00 mm
Height	20,0 mm
Width	20,0 mm

DOWNLOAD DATA

DOWNLOAD DATA


User instruction



Advertisements



Advertisements

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321681898	Folding box 1	142 mm x 42 mm x 42 mm	42.00 g	0.25 dm ³
4008321681904	Shipping box 12	180 mm x 164 mm x 136 mm	586.00 g	4.01 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

– For more information on the system guarantee and the terms and conditions of the guarantee visit www.ledvance.com/system-guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.