

PRODUCT DATASHEET CONNECTED SENSOR REMOTE

SubstiTUBE Connected Sensor Remote | Connected Sensor Remote for LEDVANCE Connected Sensor HB and LB



Product benefits

- LEDVANCE Connected sensor remote control for easy installation
- 3 years guarantee

Product features

- Compatible with LEDVANCE Connected Sensor HB and LB (Gen 2)
- Battery included (Lithium, 3 V)



TECHNICAL DATA

Electrical data


Type of current	DC
Mains frequency	5060 Hz

Light technical data

Beam angle

15°

Dimensions & Weight



Product weight	60.00 g

Lifespan

Lifespan	0 relevant
----------	------------

Additional product data

Mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	No

Certificates & Standards

Type of protection	IP20
Standards	CE

Country-specific categorizations

Order reference CONNECTED SENSO

Energy labelling regulation data acc EU 2019/2015

Length	58.0 mm
Height	8.00 mm
Width	94.00 mm

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075374034	Folding box 1	16 mm x 71 mm x 136 mm	24.00 g	0.15 dm³
4058075374041	Shipping box 10	143 mm x 78 mm x 172 mm	277.00 g	1.92 dm ³
4058075396357	Shipping box 60	486 mm x 156 mm x 192 mm	1830.00 g	14.56 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

- For Guarantee see www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.