

PRODUCT DATASHEET

SMART + WIFI PLANON 1200X300

SMART+ Planon Frameless TW and Multicolor | Frameless panel luminaires with WiFi technology

Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- RGB color control, approx. 16 million color options adjustable
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

Nominal wattage	40.00 W
Nominal voltage	220...240 V
Nominal current	203.5 mA
Mains frequency	50...60 Hz
Power factor λ	> 0.90
Operating mode	Mains voltage

Photometrical data

Light color (designation)	Tunable White / RGB
Standard deviation of color matching	< 6 sdcn
Nominal luminous flux	3300 lm
Luminous flux	3300 lm
Luminous efficacy	83 lm/W
Color temperature	3000...6500 K
Color rendering index Ra	> 80

Light technical data

Beam angle	110 °
------------	-------

Dimensions & Weight

Product weight	5020.00 g
Length	1200.00 mm
Width	300.00 mm
Height	62.00 mm

Lifespan

Number of switching cycles	15000
Lifespan	25000 h

Colors & materials

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polymethylmethacrylate (PMMA)
Light emitting surface material	PMMA

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Mounting location	Ceiling

Capabilities

Dimmable	Yes
Type of connection	Terminal, 2-Pole (L, N)
Compatible smart home technology	Google Assistant / Amazon Alexa
LED module replaceable	Not replaceable



Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Protection class	II
Type of protection	IP20

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075484511	Folding box 1	95 mm x 1,237 mm x 335 mm	5489.00 g	39.37 dm ³
4058075484528	Shipping box 3	1,250 mm x 302 mm x 367 mm	18116.00 g	138.54 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.