# PRODUCT DATASHEET SMART + WIFI PLANON 600X100

SMART+ Planon Frameless TW | Frameless panel luminaires with WiFi technology

#### Areas of application

- Indoor applications

- Kitchens, living rooms, children's rooms or home offices



#### **Product benefits**

- Easy and quick installation

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android<sup>™</sup> 4.4 or iOS 9.0)
- Dimmable
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Network protocol: WiFi



#### **TECHNICAL DATA**

### **Electrical data**

| Nominal wattage        | 28.00 W       |
|------------------------|---------------|
| Nominal voltage        | 220240 V      |
| Nominal current        | 137.5 mA      |
| Mains frequency        | 5060 Hz       |
| Power factor $\lambda$ | > 0.90        |
| Operating mode         | Mains voltage |

#### Photometrical data

| Light color (designation)            | Tunable White |
|--------------------------------------|---------------|
| Standard deviation of color matching | < 6 sdcm      |
| Nominal luminous flux                | 1800 lm       |
| Luminous flux                        | 1800 lm       |
| Luminous efficacy                    | 64 lm/W       |
| Color temperature                    | 30006500 K    |
| Color rendering index Ra             | > 80          |

# Light technical data

| Beam angle | 110 ° |
|------------|-------|
|------------|-------|

## **Dimensions & Weight**



| Product weight | 1420.00 g |
|----------------|-----------|
| Length         | 600.00 mm |
| Width          | 100.00 mm |
| Height         | 65.00 mm  |

## Lifespan

| Number of switching cycles | 15000   |
|----------------------------|---------|
| Lifespan                   | 25000 h |

## Colors & materials

| Product color                   | White                         |  |
|---------------------------------|-------------------------------|--|
| Housing color                   | White                         |  |
| Body material                   | Aluminum                      |  |
| Cover material                  | Polymethylmethacrylate (PMMA) |  |
| Light emitting surface material | РММА                          |  |

## Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
|                           |           |

#### Additional product data

| Product remark    | Reset settings to default by switching the product on for three seconds<br>and off for three seconds and repeating this five times. |  |
|-------------------|---|--|
| Mounting location | Ceiling   |  |

#### Capabilities

| Dimmable                         | Yes                             |
|----------------------------------|---------------------------------|
| Type of connection               | Terminal, 2-Pole (L, N)         |
| Compatible smart home technology | Google Assistant / Amazon Alexa |
| LED module replaceable           | Not replaceable                 |

#### **Certificates & Standards**

| Standards          | CE / EAC / REACH / RoHS |
|--------------------|-------------------------|
| Protection class   | Ш                       |
| Type of protection | IP20                    |

## **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

#### **DOWNLOAD DATA**

|     | DOWNLOAD DATA              |
|-----|----------------------------|
| PDF | User instruction           |
| PDF | Declarations of conformity |

# LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075484610 | Folding box<br>1             | 88 mm x 623 mm x 128 mm              | 1581.00 g    | 7.02 dm <sup>3</sup>  |
| 4058075484627 | Shipping box<br>6            | 662 mm x 307 mm x 310 mm             | 10645.00 g   | 63.00 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.