

# PRODUCT DATASHEET SMART + WIFI ORBIS Cromo 500 CR

Cromo | Decorative ceiling luminaires with WiFi technology



# Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices

### **Product benefits**

- Easy and quick installation

### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K  $\,$
- Dimmable
- Network protocol: WiFi



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	34.00 W
Nominal voltage	220240 V
Nominal current	150 mA
Mains frequency	5060 Hz
Power factor $\lambda$	> 0.90
Operating mode	Mains voltage


# Photometrical data

Light color (designation)	Tunable White
Standard deviation of color matching	< 6 sdcm
Nominal luminous flux	3200 lm
Luminous flux	3200 lm
Luminous efficacy	93 lm/W
Color temperature	30006500 K
Color rendering index Ra	> 80

# Light technical data

Beam angle 142.00 °	Beam angle	142.00 °
---------------------	------------	----------

# **Dimensions & Weight**



Product weight	1197.00 g
Diameter	500.00 mm
Width	500.00 mm
Height	89.00 mm

# Lifespan



Number of switching cycles	15000
Lifespan	30000 h

### Colors & materials

Product color	White
Housing color	White
Body material	Polymethylmethacrylate (PMMA)
Cover material	Polymethylmethacrylate (PMMA)

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
Ambient temperature range	-20+40 °C

# Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Mounting location	Ceiling

# **Capabilities**

Dimmable	Yes	
Type of connection	Screw terminal	
Compatible smart home technology	Google Assistant / Amazon Alexa	
LED module replaceable  Not replaceable		

### Certificates & Standards

Standards	CE / EAC / REACH / RoHS
Protection class	l I
Type of protection	IP20

# Energy labelling regulation data acc EU 2019/2015

Displacement lactor
---------------------

# **EQUIPMENT / ACCESSORIES**

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

# **DOWNLOAD DATA**



	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations of conformity

### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075486485	Folding box 1	542 mm x 118 mm x 544 mm	1663.00 g	34.79 dm³
4058075516588	Shipping box 3	564 mm x 373 mm x 567 mm	6290.00 g	119.28 dm³
4058075486492	Shipping box 6	737 mm x 565 mm x 570 mm	12399.00 g	237.35 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.