# PRODUCT DATASHEET SMART+ Filament WiFi Classic Edison 60 5,5W E27

SMART+ WiFi Filament Edison Dimmable | Edison bulb shape with filament-style with WiFi technology



### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Dimmable
- Lifetime: up to 15,000 h



5,5W E27



### **TECHNICAL DATA**

### Electrical data

Nominal wattage	6 W
Construction wattage	6.00 W
Nominal voltage	220240 V
Nominal current	50 mA
Operating frequency	5060 Hz / 50
Mains frequency	5060 Hz
Power factor λ	> 0.50
Claimed equiv. conventional lamp power	60 W

### Photometrical data


Light color (designation)	Warm White
Lumen main.fact.at end of nom.life time	0.93
Standard deviation of color matching	≤6 sdcm
Nominal luminous flux	806 lm
Luminous flux	806 lm
Luminous efficacy	134 lm/W
Adjustable color temperature	2700 K
Color temperature	2700 K
Color rendering index Ra	80
Flickering metric (Pst LM)	1.0
Stroboscope effect metric (SVM)	0.9



# Light technical data

Beam angle	300 °
Starting time	< 0.5 s

# **Dimensions & Weight**



Product weight	46.00 g
Diameter	64.00 mm
Length	143.00 mm
Width	64.00 mm
Height	64.00 mm
Outer bulb [PICOS]	ST64

# Lifespan

Number of switching cycles	100000
Lifespan	15000 h
Lumen maintenance at end of serv	0.70

# Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

# Additional product data

Mercury-free	Yes
Product remark	All technical parameters apply to the entire lamp / Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value
Base (standard designation)	E27

# **Capabilities**





Dimmable	Yes	
Compatible smart home technology	Google Assistant / Amazon Alexa	

### Certificates & Standards

Energy efficiency class	E 1)
Energy consumption	6.00 kWh/1000h
Standards	CE
Type of protection	IP20

 $<sup>1) \ {\</sup>sf Energy \ efficiency \ class \ (EEC) \ on \ a \ scale \ of \ A \ (highest \ efficiency) \ to \ G \ (lowest \ efficiency)}$ 

# Energy labelling regulation data acc EU 2019/2015

Lighting technology used	LED
Non-directional or directional	NDLS
Mains or non-mains	MLS
Light source cap-type (or other electric interface)	E27
Connected light source (CLS)	yes
Color-tuneable light source	No
Envelope	No
High luminance light source	No
Anti-glare shield	No
Correlated colour temperature type	SINGLE_VALUE
Standby power	0.5 W
Networked standby power for CLS	0.50
Claim of equivalent power	Yes
Chromaticity coordinate x	0.463
Chromaticity coordinate y	0.420
R9 Colour rendering index	0.00
Beam angle	SPHERE_360
Survival factor	0.90
Displacement factor	0.50
LED light source replaces a fluorescent light source	No
EPREL ID	644680,644660
Model number	AC32957,AC32942,AC32957,AC32957

### **DOWNLOAD DATA**





	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations of conformity

### **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075528277	Folding box 1	111 mm x 114 mm x 169 mm	121.00 g	2.14 dm <sup>3</sup>
4058075528284	Shipping box 4	243 mm x 238 mm x 185 mm	645.00 g	10.70 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.



