

PRODUCT DATASHEET ENDURA CLASSIC CASCADE 50CM Post E27 AMB

ENDURA® CLASSIC CASCADE | Contemporary aluminium luminaires with amber or clear colored glass diffusor



Areas of application

- Building facades
- Patios, balconies
- Pathway lighting
- Driveways

Product benefits

- $\,$ $\,$ High flexibility in the choice of the light source thanks to E27 base
- Easy and quick installation

Product features

- Direct illumination
- Light cover material: glass
- Light cover appearance: amber or clear
- Housing material: aluminum
- Housing color: RAL 7016
- Type of protection: IP44



TECHNICAL DATA

Electrical data


Nominal voltage	220240 V
Mains frequency	5060 Hz
Operating mode	Mains voltage

Photometrical data

Luminous efficacy	lm/W

Dimensions & Weight

Length	200.00 mm
Width	160.00 mm
Height	500.00 mm
Product weight	1540.00 g



Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum
Cover material	Glass
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20+40 °C
Type of connection	Terminal, 3-Pole (L, N, PE)

Dimmable	No
Mounting type	Surface
Mounting location	Ground
Holder designation	E27

Certificates & Standards

Additional product data

Product remark	Maximum bulb wattage: 25 W
----------------	----------------------------

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- No light sources included

DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction ENDURA CLASSIC CASCADE
PDF	Declarations of conformity EC_ENDURA CLASSIC PIPE_ENDURA CLASSIC CASCADE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075554290	Folding box 1	180 mm x 220 mm x 520 mm	1752.00 g	20.59 dm ³
4058075554306	Shipping box 2	540 mm x 380 mm x 240 mm	4609.00 g	49.25 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.