# PRODUCT DATASHEET ENDURA CLASSIC BEAM Wall updown GU10

ENDURA® BEAM | GU10 socketed luminaires with classic shape and light outlet up and down



### Areas of application

- Building facades
- Entrance lighting
- Patios, balconies
- Pathway lighting
- Driveways

### **Product benefits**

- High flexibility in the choice of the light source thanks to GU10 base
- Easy and quick installation

#### **Product features**

- Indirect illumination
- Housing material: aluminum
- Housing color: RAL 7016
- Type of protection: IP44



# **TECHNICAL DATA**

# Electrical data


| Nominal voltage | 220240 V      |
|-----------------|---------------|
| Mains frequency | 5060 Hz       |
| Operating mode  | Mains voltage |

# Photometrical data

| Luminous efficacy | lm/W |
|-------------------|------|
| Lummous emcacy    | unyw |

# **Dimensions & Weight**

| Length         | 104.00 mm |
|----------------|-----------|
| Width          | 92.00 mm  |
| Height         | 200.00 mm |
| Product weight | 791.00 g  |



# Materials & Colors

| Product color   | Dark gray |
|-----------------|-----------|
| Housing color   | Dark gray |
| Body material   | Aluminum  |
| Cover material  | Glass     |
| Mercury content | 0.0 mg    |

# **Application & Mounting**

| Ambient temperature range | -20+40 °C                   |
|---------------------------|-----------------------------|
| Type of connection        | Terminal, 3-Pole (L, N, PE) |
| Dimmable                  | No                          |

| Mounting type      | Surface |
|--------------------|---------|
| Mounting location  | Wall    |
| Holder designation | GU10    |

#### Certificates & Standards

| Standards | CE / EAC / RoHS / REACH |
|-----------|-------------------------|
|-----------|-------------------------|

### Additional product data

| Product remark Maximum bulb wattage: 2 x 35 W |
|-----------------------------------------------|
|-----------------------------------------------|

# **EQUIPMENT / ACCESSORIES**

- Complete mounting and connecting accessories included
- No light sources included

#### **DOWNLOAD DATA**

|     | DOWNLOAD DATA                   |
|-----|---------------------------------|
| PDF | User instruction ENDURA CLASSIC |
| PDF | Declarations of conformity      |

## LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume    |
|---------------|------------------------------|--------------------------------------|--------------|-----------|
| 4058075554573 | Folding box<br>1             | 100 mm x 110 mm x 210 mm             | 867.00 g     | 2.31 dm³  |
| 4058075554580 | Shipping box<br>4            | 245 mm x 220 mm x 235 mm             | 3813.00 g    | 12.67 dm³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.