# PRODUCT DATASHEET SMART+ WIFI ORBIS MAGNET 300X300mm Black

Magnet | Smart decorative ceiling with wifi technology TW and dimmable



- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



## **Product benefits**

- Easy and quick installation
- Magnetic closure
- No screw visible

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



September 16, 2022, 11:53:38 SMART+ WIFI ORBIS MAGNET 300X300mm Black

## **TECHNICAL DATA**

## **Electrical data**

Nominal wattage	26.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	115.000 mA	
Inrush current	1.08 A	
Power factor $\lambda$	> 0.90	
Total harmonic distortion	< 20 %	
Protection class	I	
Operating mode	External LED driver	

## Photometrical data

Luminous flux	2500 lm	
Total luminous flux of contained light sources	2800 lm	
Luminous efficacy	96 lm/W	
Color temperature	30006500 K	
Light color (designation)	Tunable White	
Color rendering index Ra	≥80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RGO	
Photobiological safety group acc. to EN62471	RGO	
Beam angle	110 °	

## **Dimensions & Weight**

Length	300.00 mm
Width	300.00 mm
Height	86.00 mm
Product weight	1130.00 g

## Materials & Colors

Product color	Black
Housing color	Black
Body material	Steel
Cover material	Polycarbonate (PC)
Mercury content	0.0 mg

# Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Screw terminal	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
LED module replaceable	Not replaceable	

## Lifespan

Lifespan L70/B50 at 25 °C	30000 h	
Number of switching cycles	15000	

#### **Emergency lighting**

Type of emergency operation test	None
Integrated test switch	No

# **Certificates & Standards**

Standards	CE / UKCA	
Luminaire with limited surface temperature, "D sign"	No	

# EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

## DOWNLOAD DATA

	DOWNLOAD DATA
PDF	User instruction
PDF	Declarations of conformity

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075572737	Folding box 1	352 mm x 112 mm x 352 mm	1380.00 g	13.88 dm³
4058075572744	Shipping box 4	462 mm x 368 mm x 370 mm	6663.00 g	62.91 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.