

PRODUCT DATASHEET SMART+ WIFI ORBIS GAVIN 500mm

Gavin | Smart ceiling luminaires with main light and WiFi technology



Areas of application

- Indoor applications

- Kitchens, living rooms, children's rooms or home offices

Product benefits

- Easy and quick installation

Product features

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android[™] 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Dimmable
- Network protocol: WiFi



TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W	
Nominal voltage	220240 V	
Mains frequency	5060 Hz	
Nominal current	154.000 mA	
Inrush current	40 A	
Power factor λ	> 0.5	
Total harmonic distortion	< 20 %	
Protection class	П	
Operating mode	External LED driver	

Photometrical data

Luminous flux	3300 lm	
Total luminous flux of contained light sources	3300 lm	
Luminous efficacy	110 lm/W	
Color temperature	2700 К	
Light color (designation)	Tunable White	
Color rendering index Ra	> 80	
Standard deviation of color matching	< 6 sdcm	
Photobiological safety group acc. to EN62778	RG1	
Photobiological safety group acc. to EN62471	RGO	
Beam angle	120 °	

Dimensions & Weight

Diameter	484.00 mm
Height	85.00 mm
Product weight	1270.00 g

Materials & Colors

Product color

Black



Housing color	Black	
Body material	Steel	
Cover material	Polycarbonate (PC)	
Mercury content	0.0 mg	

Application & Mounting

Ambient temperature range	-20+40 °C	
Temperature range at storage	-20+80 °C	
Type of connection	Screw terminal	
Type of protection	IP20	
Protection class IK (shock resistance)	IK03	
Dimmable	Yes	
Type of dimming	WiFi	
Mounting type	Surface	
Mounting location	Ceiling	
Application environment	Indoor	
LED module replaceable	Not replaceable	

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	15000

Emergency lighting

Type of emergency operation test	None
Integrated test switch	No

Certificates & Standards

Standards	CE / UKCA	
Luminaire with limited surface temperature, "D sign"	No	

EQUIPMENT / ACCESSORIES

- Mounting bracket included
- Mounting screws and dowels included
- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

	DOWNLOAD DATA
POF	User instruction
PDF	Declarations of conformity

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075573512	Folding box 1	528 mm x 103 mm x 533 mm	1858.00 g	28.99 dm³
4058075573529	Shipping box 5	546 mm x 531 mm x 562 mm	10759.00 g	162.94 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

