

PRODUCT DATASHEET

LED WORKLIGHT BATTERY 67CM Tube

WORKLIGHTS BATTERY | Mobile battery powered worklight



Areas of application

- Renovation
- Garages
- Basement
- Workshops

Product benefits

- Energy savings of up to 80% compared to halogen lamp worklights
- Independent of power supply due to battery technology

Product features

- Worklight with swiveling head
- Battery discharge time: up to 4 h
- Battery rechargeable via USB cable



TECHNICAL DATA

Electrical data

| | |
|--|------------|
| Nominal wattage | 10 W |
| Nominal voltage | 5 V |
| Mains frequency | 50...60 Hz |
| Nominal current | 129 mA |
| Inrush current | 60 A |
| Max. no. of lum. on circuit break. B16 A | 3 |
| Max. no. of lum. on circuit break. C10 A | 3 |
| Max. no. of lum. on circuit break. C16 A | 6 |
| Power factor λ | > 0.4 |
| Protection class | III |
| Operating mode | Battery |

Photometrical data

| | |
|--|------------|
| Luminous flux | 800 lm |
| Luminous efficacy | 80 lm/W |
| Color temperature | 4000 K |
| Light color (designation) | Cool White |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | < 6 sdcm |
| Flickering metric (Pst LM) | ≤ 1 % |
| Stroboscope effect metric (SVM) | ≤ 0.4 |
| Photobiological safety group acc. to EN62778 | RG1 |
| Photobiological safety group acc. to EN62471 | RG1 |
| Beam angle | 110 ° |

Dimensions & Weight

| | |
|----------------|-----------|
| Length | 704.00 mm |
| Width | 72.00 mm |
| Height | 42.00 mm |
| Product weight | 586.00 g |

Materials & Colors

| | |
|-----------------|--------------------|
| Product color | Orange |
| Housing color | Orange |
| Body material | Plastic |
| Cover material | Polycarbonate (PC) |
| Mercury content | 0.0 mg |

Application & Mounting

| | |
|--|-----------------|
| Ambient temperature range | -10...+40 °C |
| Temperature range at storage | -20...+50 °C |
| Type of protection | IP54 |
| Protection class IK (shock resistance) | IK04 |
| Dimmable | No |
| Mounting type | Standing |
| Mounting location | Floor |
| LED module replaceable | Not replaceable |

Lifespan

| | |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C | 25000 h |
| Number of switching cycles | 15000 |

Emergency lighting

| | |
|---|--------|
| Luminous flux in emergency operation mode | 800 lm |
| Nominal voltage of battery | 5 V |
| Battery life in emergency operation mode | 4 h |
| Battery charging time | 3 h |

Certificates & Standards

| | |
|--|-------------------|
| Standards | RoHS / REACH / CE |
| Luminaire with limited surface temperature, "D sign" | No |

EQUIPMENT / ACCESSORIES

- USB charging cable

DOWNLOAD DATA

DOWNLOAD DATA



User instruction
LED WORKLIGHT BATT TUBE 67CM



Declarations of conformity
LED WORKLIGHT BATT TUBE 67CM

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075576551 | Folding box 1 | 56 mm x 81 mm x 768 mm | 856.00 g | 3.48 dm ³ |
| 4058075576568 | Shipping box 4 | 792 mm x 182 mm x 138 mm | 3906.00 g | 19.89 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.