


# PRODUCT DATASHEET

## PLANON PLUS 600X600mm 3000K

PLANON™ Plus | Slim panel luminaires for surface mounting



---

### Areas of application

- For indoor use only
- Decorative domestic lighting
- Ceilings

---

### Product benefits

- Very homogenous light
- Quick and simple installation by one person

---

### Product features

- Ceiling luminaire with advanced LED technology



---

## TECHNICAL DATA

### Electrical data

|                           |             |
|---------------------------|-------------|
| Nominal wattage           | 36.00 W     |
| Nominal voltage           | 220...240 V |
| Power factor $\lambda$    | > 0.90      |
| Total harmonic distortion | < 20 %      |
| Protection class          | I           |

### Photometrical data

|  |            |
|--|------------|
| Luminous flux                                | 2800 lm    |
| Luminous efficacy                            | 78 lm/W    |
| Color temperature                            | 3000 K     |
| Light color (designation)                    | Warm White |
| Color rendering index Ra                     | $\geq 80$  |
| Standard deviation of color matching         | < 6 sdcms  |
| Photobiological safety group acc. to EN62778 | RG1        |
| Photobiological safety group acc. to EN62471 | RG0        |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Length         | 595.00 mm |
| Width          | 595.00 mm |
| Height         | 56.00 mm  |
| Product weight | 3420.00 g |

### Materials & Colors

|                 |          |
|-----------------|----------|
| Product color   | White    |
| Housing color   | White    |
| Body material   | Aluminum |
| Mercury content | 0.0 mg   |

### Application & Mounting

|                              |                 |
|------------------------------|-----------------|
| Ambient temperature range    | -20...+40 °C    |
| Temperature range at storage | -20...+80 °C    |
| Type of connection           | Screw terminal  |
| Type of protection           | IP20            |
| Dimmable                     | No              |
| Mounting type                | Surface         |
| Mounting location            | Ceiling         |
| Application environment      | Indoor          |
| LED module replaceable       | Not replaceable |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 15000   |


### Certificates & Standards

|  |                                      |
|--|--------------------------------------|
| Standards  | CE / EMC / ERP / RoHS / REACH / UKCA |
| Luminaire with limited surface temperature, "D sign" | No                                   |

### EQUIPMENT / ACCESSORIES

– Pre-assembled mounting kit, screws and dowels included

### DOWNLOAD DATA

| DOWNLOAD DATA  |  |
|--|--|
|  | User instruction<br>PLANON PLUS 120x30 30x60 60x60 |

### LOGISTICAL DATA

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                 |
|---------------|------------------------------|--------------------------------------|--------------|------------------------|
| 4058075601291 | Folding box<br>1             | 76 mm x 622 mm x 622 mm              | 3952.00 g    | 29.40 dm <sup>3</sup>  |
| 4058075601307 | Shipping box<br>3            | 640 mm x 249 mm x 655 mm             | 12806.00 g   | 104.38 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.