

# PRODUCT DATASHEET SMART+ WIFI SPOT R50 40 3.3W 2700...6500K E14

SMART+ SPOT CONCENTRA Tunable White | SMART+ SPOT CONCENTRA LAMPS WITH WIFI TECHNOLOGY



#### Areas of application

- General illumination
- Residential interiors
- Professional (hotels, bars, boutiques etc.)
- Outdoor use in suitable outdoor luminaires only

#### **Product benefits**

- Wireless control via app
- Easy to install and use
- Contains no mercury

#### **Product features**

- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 9.0)
- Controllable via Google Assistant and Amazon Alexa possible
- Network protocol: WiFi
- Adjustable light color via Tunable White: Warm White to Cool White (2,700 K...6,500 K)
- Dimmable
- Lifetime: up to 20,000 h



## **TECHNICAL DATA**

## Electrical data

| Nominal wattage                        | 3.3 W   |
|--|---------|
| Construction wattage                   | 3.30 W  |
| Nominal voltage                        | 220 V   |
| Nominal current                        | 30 mA   |
| Operating frequency                    | 5060 Hz |
| Mains frequency                        | 5060 Hz |
| Power factor λ                         | > 0.50  |
| Claimed equiv. conventional lamp power | 40 W    |

## Photometrical data

| Light color (designation)               | Tunable White |
|---|---------------|
| Lumen main.fact.at end of nom.life time | 0.70          |
| Standard deviation of color matching    | ≤6 sdcm       |
| Nominal luminous flux                   | 210 lm        |
| Luminous flux                           | 210 lm        |
| Luminous efficacy                       | 63 lm/W       |
| Luminous intensity                      | 245 cd        |
| Adjustable color temperature            | 27006500 K    |
| Color temperature                       | 27006500 K    |
| Color rendering index Ra                | 80            |



# Light technical data

| Beam angle          | 45 °     |
|---------------------|----------|
| Starting time       | < 0.5 s  |
| Warm-up time (60 %) | < 0.50 s |



## **Dimensions & Weight**

| Product weight     | 50.00 g  |
|--------------------|----------|
| Diameter           | 50.00 mm |
| Maximum diameter   | 50 mm    |
| Length             | 85.00 mm |
| Width              | 50.00 mm |
| Height             | 50.00 mm |
| Outer bulb [PICOS] | T50      |

#### Lifespan

| Number of switching cycles       | 100000 |
|----------------------------------|--------|
| Lumen maintenance at end of serv | 0.70   |

## Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
|---------------------------|-----------|

## Additional product data

| Base (standard designation) | E14 |
|-----------------------------|-----|
|-----------------------------|-----|

## **Capabilities**

| Dimmable                         | Yes                             |
|----------------------------------|---------------------------------|
| Compatible smart home technology | Google Assistant / Amazon Alexa |

#### Certificates & Standards

| Energy efficiency class | G <sup>1)</sup> |
|-------------------------|-----------------|
| Energy consumption      | 4.00 kWh/1000h  |
| Standards               | CE              |

<sup>1)</sup> Energy efficiency class (EEC) on a scale of A (highest efficiency) to G (lowest efficiency)

# Energy labelling regulation data acc EU 2019/2015

| Lighting technology used       | LED |
|--------------------------------|-----|
| Non-directional or directional | DLS |

| Mains or non-mains                                   | MLS             |
|--|-----------------|
| Light source cap-type (or other electric interface)  | E14             |
| Connected light source (CLS)                         | yes             |
| Color-tuneable light source                          | yes             |
| Envelope   | No              |
| High luminance light source                          | No              |
| Anti-glare shield                                    | No              |
| Correlated colour temperature type                   | RANGE           |
| Claim of equivalent power                            | Yes             |
| R9 Colour rendering index                            | 0.00            |
| Beam angle correspondence                            | NARROW_CONE_90  |
| LED light source replaces a fluorescent light source | No              |
| EPREL ID   | 528228          |
| Model number   | AC33941,AC33941 |

#### **DOWNLOAD DATA**

|     | DOWNLOAD DATA              |
|-----|----------------------------|
| PDF | Declarations of conformity |
| PDF | Installation guide         |
| PDF | Installation guide         |

#### **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075609518 | Folding box<br>1             | 61 mm x 96 mm x 154 mm               | 124.00 g     | 0.90 dm³             |
| 4058075609525 | Shipping box<br>4            | 210 mm x 165 mm x 135 mm             | 629.00 g     | 4.68 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.