

# PRODUCT DATASHEET

## SUN@Home Downlight Slim 120mm

Sun@Home Downlights | Downlight with Human Centric Lighting Technology

---

### Areas of application

- Indoor applications
- Kitchens, living rooms, children's rooms or home offices



---

### Product benefits

- Enable increased concentration and efficiency
- Improve overall activity level and daytime alertness
- Improve sleeping rhythm and -intensity
- Improve optic convenience
- Enables an improved level of clean-air-safety by killing residential germs and bad odors
- Homogenous light distribution
- Easy and quick installation

---

### Product features

- Adjustable color temperature via Tunable White: 2,200...5,000 K
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Dimmable
- Innovative Fullspectrum SunLike LEDs with CRI95
- SunLike LEDs with reduced Blue Light in LED Spectrum



- Innovative luminaire coating-technology fighting household germs and odors
- Automated biorhythm feature



## TECHNICAL DATA

### Electrical data

|                        |               |
|------------------------|---------------|
| Nominal wattage        | 8.00 W        |
| Nominal voltage        | 220...240 V   |
| Mains frequency        | 50...60 Hz    |
| Nominal current        | 80.000 mA     |
| Inrush current         | 30 A          |
| Power factor $\lambda$ | $\geq 0.5$    |
| Protection class       | II            |
| Operating mode         | Mains voltage |

### Photometrical data

|  |               |
|--|---------------|
| Luminous flux                                  | 400 lm        |
| Total luminous flux of contained light sources | 700 lm        |
| Luminous efficacy                              | 50 lm/W       |
| Color temperature                              | 2200...5000 K |
| Light color (designation)                      | Tunable White |
| Color rendering index Ra                       | > 95          |
| Standard deviation of color matching           | $\leq 6$ sdcn |
| Photobiological safety group acc. to EN62778   | RG0           |
| Photobiological safety group acc. to EN62471   | RG0           |
| Beam angle                                     | 110 °         |

### Dimensions & Weight

|                |           |
|----------------|-----------|
| Diameter       | 120.00 mm |
| Width          | 120.00 mm |
| Height         | 35.00 mm  |
| Product weight | 107.00 g  |

### Materials & Colors

|               |       |
|---------------|-------|
| Product color | White |
|---------------|-------|



|                 |                  |
|-----------------|------------------|
| Housing color   | White            |
| Body material   | Plastic          |
| Cover material  | Polystyrene (PS) |
| Mercury content | 0.0 mg           |

### Application & Mounting

|                              |                 |
|------------------------------|-----------------|
| Ambient temperature range    | -20...+40 °C    |
| Temperature range at storage | -20...+60 °C    |
| Type of connection           | Terminal        |
| Type of protection           | IP20            |
| Dimmable                     | Yes             |
| Type of dimming              | WiFi            |
| Mounting type                | Recessed        |
| Mounting location            | Ceiling         |
| Application environment      | Indoor          |
| Mounting diameter            | 105.00 mm       |
| LED module replaceable       | Not replaceable |
| With light source            | Yes             |

### Lifespan

|                            |         |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |
| Number of switching cycles | 15000   |

### Emergency lighting

|  |   |
|--|---|
| Luminous flux in maintained operation mode | - |
|--|---|

### Certificates & Standards










|  |           |
|--|-----------|
| Standards  | CE / UKCA |
| Luminaire with limited surface temperature, "D sign" | No        |

### EQUIPMENT / ACCESSORIES

- Control via app or voice control requires compatible Smart home system
- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required
- Complete mounting and connecting accessories included

### DOWNLOAD DATA



| DOWNLOAD DATA   |                               |
|---|-------------------------------|
|   | User instruction              |
|   | Declarations Of Conformity CE |
|   | Catalogs                      |
|   | Catalogs                      |
|   | Catalogs                      |
|   | Catalogs                      |
|   | Catalogs                      |
|   | Catalogs                      |
|  | Packaging insert              |

**LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume                |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075627024 | Folding box<br>1             | 127 mm x 127 mm x 58 mm              | 156.00 g     | 0.94 dm <sup>3</sup>  |
| 4058075627031 | Shipping box<br>6            | 262 mm x 134 mm x 186 mm             | 1071.00 g    | 6.53 dm <sup>3</sup>  |
| 4058075657090 | Shipping box<br>24           | 542 mm x 286 mm x 209 mm             | 4929.00 g    | 32.40 dm <sup>3</sup> |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

