


# PRODUCT DATASHEET

## ORBIS IP44 SENSOR 400MM 25W 830

ORBIS® IP44 | Splash-proof LED ceiling luminaire with sensor



---

### Areas of application

- Entrances / Hallways
- Bathrooms
- Ceiling and wall surface mounting
- Outdoor use (roofed areas) in residential sector

---

### Product benefits

- Very homogenous light
- Easy and quick installation

---

### Product features

- Ceiling luminaire with advanced LED technology
- Circular light emission
- Type of protection: IP44
- Adjustable daylight and infrared presence sensor



## TECHNICAL DATA

### Electrical data

Nominal wattage	25.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	185 mA
Inrush current	9.1 A
Max. no. of lum. on circuit break. B16 A	18
Max. no. of lum. on circuit break. C10 A	18
Max. no. of lum. on circuit break. C16 A	29
Power factor $\lambda$	> 0.5
Protection class	I
Operating mode	External LED driver

### Photometrical data

Luminous flux	1800 lm
Total luminous flux of contained light sources	2700 lm
Luminous efficacy	80 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Photobiological safety group acc. to EN62778	RG1
Photobiological safety group acc. to EN62471	RG0
Beam angle	120 °

### Dimensions & Weight

Diameter	400 mm
Height	83.00 mm
Product weight	695.00 g

### Materials & Colors

Product color	White
Housing color	White
Body material	Aluminum
Cover material	Polycarbonate (PC)

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Temperature range at storage	-20...+70 °C
Type of connection	Terminal, 3-Pole (L, N, PE)
Type of protection	IP44
Protection class IK (shock resistance)	IK03
Dimmable	No
Mounting type	Surface
Mounting location	Ceiling
Application environment	Indoor
LED module replaceable	Not replaceable

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

### Emergency lighting

Type of emergency light operation	Non-maintained
Luminous flux in maintained operation mode	-
Luminous flux in emergency operation mode	-

### Certificates & Standards

Standards	CE / UKCA
-----------	-----------

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### DOWNLOAD DATA

DOWNLOAD DATA	
---------------	--



User instruction

### LOGISTICAL DATA



Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075651852	Folding box 1	94 mm x 429 mm x 429 mm	836.00 g	17.30 dm <sup>3</sup>
4058075651869	Shipping box 5	482 mm x 447 mm x 459 mm	5129.00 g	98.89 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

