


# PRODUCT DATASHEET

## DECOR PERCHERO 800mm WOOD

Decor Perchero | Decorative luminaires with hanger and light



---

### Areas of application

- Bedrooms
- Entrance areas
- Offices

---

### Product benefits

- Elegant design
- Soft light thanks to indirect light distribution

---

### Product features

- Possibility to hang up the clothing
- Wall Luminaire
- 3000 K
- Housing material: metal

## TECHNICAL DATA

### Electrical data


Nominal wattage	6.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	36.000 mA
Inrush current time $T_{h50}$	1800 $\mu$ s
Max. no. of lum. on circuit break. B16 A	29
Max. no. of lum. on circuit break. C16 A	49
Power factor $\lambda$	$\geq 0.5$
Total harmonic distortion	< 70 %
Protection class	II

### Photometrical data

Luminous flux	80 lm
Total luminous flux of contained light sources	620 lm
Luminous efficacy	13 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdc <sub>m</sub>
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0

### Dimensions & Weight

Length	800.00 mm
Width	50.00 mm
Height	200.00 mm
Product weight	900.00 g



### Materials & Colors

Product color	Black
---------------	-------

Housing color	Black
Body material	Steel
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Terminal, 2-Pole (L, N)
Type of protection	IP20
Dimmable	No
Mounting type	Surface
Application environment	Indoor
LED module replaceable	Not replaceable

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	30000


### Certificates & Standards

Standards	CE / UKCA
Ball shot safe	No

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075756786	Folding box 1	74 mm x 232 mm x 263 mm	987.00 g	4.52 dm <sup>3</sup>
4058075756793	Shipping box 4	315 mm x 253 mm x 288 mm	4346.00 g	22.95 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.