

PRODUCT DATASHEET DECOR PERCHERO 850mm IP44 CHROME

Decor Perchero | Decorative luminaires with hanger and light



Areas of application

- Bedrooms
- Entrance areas
- Offices

Product benefits

- Elegant design
- Soft light thanks to indirect light distribution

Product features

- Possibility to hang up the clothing
- Wall Luminaire
- 3000 K
- Housing material: metal

TECHNICAL DATA

Electrical data


| Nominal wattage | 12.00 W |
|--|-----------|
| Nominal voltage | 220240 V |
| Mains frequency | 5060 Hz |
| Nominal current | 58.000 mA |
| Inrush current time T _{h50} | 1900 μs |
| Max. no. of lum. on circuit break. B16 A | 30 |
| Max. no. of lum. on circuit break. C16 A | 50 |
| Power factor λ | ≥0.7 |
| Total harmonic distortion | < 70 % |
| Protection class | П |

Photometrical data

| Luminous flux | 800 lm |
|--|------------|
| Total luminous flux of contained light sources | 1300 lm |
| Luminous efficacy | 66 lm/W |
| Color temperature | 3000 K |
| Light color (designation) | Warm White |
| Color rendering index Ra | > 80 |
| Standard deviation of color matching | 6 sdcm |
| Flickering metric (Pst LM) | - |
| Stroboscope effect metric (SVM) | - |
| Photobiological safety group acc. to EN62778 | RGO |

Dimensions & Weight

| Length | 850.00 mm |
|----------------|-----------|
| Width | 55.00 mm |
| Height | 195.00 mm |
| Product weight | 950.00 g |



Materials & Colors

| Product color | Silver |
|---------------|--------|
| | _ |

| Housing color | Silver |
|--|--------|
| Body material | Steel |
| Glow Wire Test according to IEC 60695-2-12 | 650 °C |
| Mercury content | 0.0 mg |

Application & Mounting

| Ambient temperature range | -20+40 °C |
|---------------------------|-------------------------|
| Type of connection | Terminal, 2-Pole (L, N) |
| Type of protection | IP44 |
| Dimmable | No |
| Mounting type | Surface |
| Application environment | Indoor |
| LED module replaceable | Not replaceable |

Lifespan

| Lifespan L70/B50 at 25 °C | 30000 h |
|----------------------------|---------|
| Number of switching cycles | 30000 |

Certificates & Standards

| Standards | CE / UKCA |
|----------------|-----------|
| Ball shot safe | No |

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

DOWNLOAD DATA

DOWNLOAD DATA



User instruction

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|-----------------------|
| 4058075756885 | Folding box 1 | 82 mm x 922 mm x 233 mm | 1222.00 g | 17.62 dm³ |
| 4058075756892 | Shipping box 4 | 945 mm x 253 mm x 350 mm | 5838.00 g | 83.68 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.