

# PRODUCT DATASHEET

## SMART+ Wifi Decor Wood Table TW

Smart+ Wood | Smart+ Decor design luminaires with WiFi technology



---

### Areas of application

- Entrance areas
- Living rooms
- Bedrooms
- Offices

---

### Product benefits

- Elegant design

---

### Product features

- Adjustable color temperature via Tunable White: 3,000...6,500 K
- Controllable via LEDVANCE SMART+ WiFi App (with minimum Android™ 4.4 or iOS 10.0)
- Controllable via voice control available: Google Assistant or Amazon Alexa
- Decorative Luminaire
- Housing material: metal and wood



## TECHNICAL DATA

### Electrical data


Nominal wattage	8.00 W
Nominal voltage	220...240 V
Mains frequency	50...60 Hz
Nominal current	43.000 mA
Inrush current	2.82 A
Inrush current time $T_{h50}$	1600 $\mu$ s
Max. no. of lum. on circuit break. B16 A	30
Max. no. of lum. on circuit break. C16 A	51
Power factor $\lambda$	$\geq 0.5$
Total harmonic distortion	< 20 %
Protection class	II

### Photometrical data

Luminous flux	350 lm
Total luminous flux of contained light sources	650 lm
Luminous efficacy	43 lm/W
Color temperature	3000...6500 K
Light color (designation)	Tunable White
Color rendering index Ra	> 80
Standard deviation of color matching	< 6 sdc
Photobiological safety group acc. to EN62778	RG0
Photobiological safety group acc. to EN62471	RG0

### Dimensions & Weight

Length	150.00 mm
Width	150.00 mm
Height	458.00 mm
Product weight	1200.00 g
Cable length	1800 mm



### Materials & Colors

Product color	Black
Housing color	Black
Body material	Wood
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of connection	Plug type C (EU)
Type of protection	IP20
Dimmable	Yes
Type of dimming	WiFi
Mounting type	Standing
Application environment	Indoor
Adjustable	No
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	30000 h
Number of switching cycles	15000

### Certificates & Standards

Standards	CE / UKCA
Ball shot safe	No




### Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Number of illuminants	1

### EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

### DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction
	Declarations of conformity
	Installation guide

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075757585	Folding box 1	172 mm x 482 mm x 173 mm	1347.00 g	14.34 dm <sup>3</sup>
4058075757592	Shipping box 4	365 mm x 365 mm x 510 mm	6109.00 g	67.94 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.