

# PRODUCT DATASHEET

## ENDURA STYLE SOLAR GLOW

Endura Style solar GLOW | Outdoor Endura Style Solar Glow sensor



---

### Areas of application

- Outdoor use (IP44)
- Garages
- Building facades

---

### Product benefits

- Easy and quick installation
- Demand based lighting and energy saving thanks to motion and daylight sensor
- High-quality materials

---

### Product features

- Solar powered outdoor LED luminaire
- PIR motion detector and daylight sensor
- Color temperature: 3,000 K (Warm White)
- Battery charging via solar panel



## TECHNICAL DATA

### Electrical data


Nominal wattage	3.60 W
Nominal voltage	3,7 V
Nominal current	840.000 mA
Protection class	III

### Photometrical data

Luminous flux	180 lm
Total luminous flux of contained light sources	420 lm
Luminous efficacy	50 lm/W
Color temperature	3000 K
Light color (designation)	Warm White
Color rendering index Ra	≥80
Standard deviation of color matching	< 6 sdcn
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0

### Dimensions & Weight

Length	160.00 mm
Width	177.00 mm
Height	80.00 mm
Product weight	520.00 g



### Materials & Colors

Product color	Dark gray
Housing color	Dark gray
Body material	Aluminum Polycarbonate (PC)
Glow Wire Test according to IEC 60695-2-12	650 °C



Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

### Sensor

Type of sensor	Motion / Daylight
Sensor detection angle	100 °
Sensor controlled switching time	30 s
Detection range of motion sensor	5...10 m
Detection threshold of daylight sensor	0...60 lx

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763210	Folding box 1	85 mm x 170 mm x 185 mm	590.00 g	2.67 dm <sup>3</sup>
4058075763227	Shipping box 2	190 mm x 190 mm x 205 mm	1404.00 g	7.40 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.