

PRODUCT DATASHEET

SMART+ BT Solar Spot Light RGB + TW

Smart+ Solar Spot Multicolor | Outdoor Smart Solar Spot & Bollard



Areas of application

- Outdoor use (IP44)
- Gardens
- Patios, balconies

Product benefits

- Easy and quick installation
- Colorful garden lighting with smart and intelligent control options
- Demand based lighting and energy saving thanks to daylight sensor
- High-quality materials
- Flexible mounting, also without use of ground spikes

Product features

- Controllable via LEDVANCE SMART+ App (with minimum Android 6.0 or iOS 11.0)
- Solar powered outdoor LED luminaire
- RGB color control, approx. 16 million color options adjustable
- Dimmable
- Battery charging via solar panel
- Network protocol: Bluetooth
- Type of protection: IP44



TECHNICAL DATA

Electrical data

Nominal wattage	0.60 W
Nominal voltage	3,7 V
Nominal current	160.000 mA
Power factor λ	> 0.5
Protection class	III

Photometrical data

Luminous flux	45 lm
Total luminous flux of contained light sources	60 lm
Luminous efficacy	75 lm/W
Color temperature	3000...6500 K
Light color (designation)	Tunable White / RGB
Color rendering index Ra	> 80
Standard deviation of color matching	6 sdcn
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0
Beam angle	58.00 °

Dimensions & Weight

Length	92.00 mm
Width	245.00 mm
Height	348.00 mm
Product weight	438.00 g



Materials & Colors

Product color	Black
Housing color	Black

Body material	Acrylonitrile butadiene styrene (ABS)
Glow Wire Test according to IEC 60695-2-12	650 °C
Mercury content	0.0 mg

Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP44
Dimmable	Yes
Type of dimming	Bluetooth
Mounting type	Ground spike
Application environment	Outdoor
Adjustable	Yes
LED module replaceable	Not replaceable
With light source	Yes

Lifespan

Lifespan L70/B50 at 25 °C	15000 h
Number of switching cycles	1000

Emergency lighting

Battery charging time	8 h
-----------------------	-----

Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

Additional product data

Product remark	Reset settings to default by switching the product on for three seconds and off for three seconds and repeating this five times.
Number of illuminants	1

EQUIPMENT / ACCESSORIES

- For control via LEDVANCE SMART + WiFi App, a smart phone or Tablet PC is required

DOWNLOAD DATA

DOWNLOAD DATA



User instruction

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075763883	Folding box 1	102 mm x 187 mm x 204 mm	564.00 g	3.89 dm ³
4058075763890	Shipping box 4	390 mm x 215 mm x 230 mm	2685.00 g	19.29 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

