

# PRODUCT DATASHEET

## ENDURA STYLE SOLAR OVAL 4000K

Endura Style solar WALL | Outdoor Endura Style Oval Wall Sensor



---

### Areas of application

- Outdoor use (IP44)
- Garages
- Building facades

---

### Product benefits

- Easy and quick installation
- Demand based lighting and energy saving thanks to motion and daylight sensor
- High-quality materials

---

### Product features

- Solar powered outdoor LED luminaire
- PIR motion detector and daylight sensor
- Available with color temperature 3000 K or 4000 K
- Battery charging via solar panel



## TECHNICAL DATA

### Electrical data


Nominal wattage	6.00 W
Nominal voltage	7,4 V
Nominal current	750.000 mA
Protection class	III

### Photometrical data

Luminous flux	540 lm
Total luminous flux of contained light sources	550 lm
Luminous efficacy	90 lm/W
Color temperature	4000 K
Light color (designation)	Cool White
Color rendering index Ra	≥80
Standard deviation of color matching	6 sdc <sub>m</sub>
Flickering metric (Pst LM)	-
Stroboscope effect metric (SVM)	-
Photobiological safety group acc. to EN62778	RG0

### Dimensions & Weight

Length	340.00 mm
Width	125.00 mm
Height	60.00 mm
Product weight	1655.00 g



### Materials & Colors

Product color	Black
Housing color	Black
Body material	Aluminum
Glow Wire Test according to IEC 60695-2-12	650 °C

Mercury content	0.0 mg
-----------------	--------

### Application & Mounting

Ambient temperature range	-20...+40 °C
Type of protection	IP44
Dimmable	No
Mounting type	Surface
Application environment	Outdoor
LED module replaceable	Not replaceable
With light source	Yes

### Lifespan

Lifespan L70/B50 at 25 °C	25000 h
Number of switching cycles	12500

### Sensor

Type of sensor	Motion / Daylight
Sensor detection angle	100 °
Sensor controlled switching time	60 s
Detection range of motion sensor	5...8 m
Detection threshold of daylight sensor	0...10 lx

### Certificates & Standards

Standards	CE / UKCA
Luminaire with limited surface temperature, "D sign"	No
Ball shot safe	No

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075766242	Folding box 1	80 mm x 360 mm x 140 mm	1752.00 g	4.03 dm <sup>3</sup>
4058075766259	Shipping box 4	380 mm x 180 mm x 310 mm	7428.00 g	21.20 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.