



### Main

|                           |  |
|---------------------------|--|
| Range                     | Asfora   |
| Product or component type | Switch   |
| Device presentation       | Mechanism with fixing frame                      |
| Load type                 | Load for energy saving lamps with ballast: 100 W |
| Colour tint               | Aluminium  |
| Type of packing           | Flow-pack  |

### Complementary

|                         |                                       |
|-------------------------|---------------------------------------|
| Device mounting         | Flush                                 |
| Switch function         | Intermediate                          |
| Number of rocker        | 1                                     |
| Power range             | 2300 W                                |
| Rated current           | 10 AX at 250 V AC                     |
| Connections - terminals | Lift terminals                        |
| Number of cables        | 2.0 cable(s) 2.5 mm <sup>2</sup>      |
| Cable stiffness         | Flexible<br>Rigid<br>Solid stranded   |
| Wire stripping length   | 13.0 mm                               |
| Material                | ABS (acrylonitrile butadiene-styrene) |
| Surface finish          | Painted                               |
| Conductor material      | Copper                                |
| Fixing mode             | Screws or claws 51...70 mm            |
| Height                  | 71 mm                                 |
| Width                   | 71 mm                                 |
| Depth                   | 43.0 mm                               |
| Projecting depth        | 15 mm                                 |
| Net weight              | 0.0679 kg                             |

### Environment

|                                       |             |
|---------------------------------------|-------------|
| Standards                             | IEC 60669-1 |
| Product certifications                | VDE         |
| Quality labels                        | CE          |
| IP degree of protection               | IP20        |
| Ambient air temperature for operation | -5...40 °C  |

### Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 4.0 cm |
| Package 1 Width              | 7.0 cm |
| Package 1 Length             | 7.0 cm |

|                              |          |
|------------------------------|----------|
| Package 1 Weight             | 69.0 g   |
| Unit Type of Package 2       | BB1      |
| Number of Units in Package 2 | 10       |
| Package 2 Height             | 9.5 cm   |
| Package 2 Width              | 18.5 cm  |
| Package 2 Length             | 27.5 cm  |
| Package 2 Weight             | 763.0 g  |
| Unit Type of Package 3       | S04      |
| Number of Units in Package 3 | 120      |
| Package 3 Height             | 30.0 cm  |
| Package 3 Width              | 40.0 cm  |
| Package 3 Length             | 60.0 cm  |
| Package 3 Weight             | 9.777 kg |

### Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |