



Main

Range	Asfora
Product or component type	Push-button
Device presentation	Complete product
Colour tint	Cream
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Number of rocker	1
Local signalling	LED
Power range	2300 W
Rated current	10 A at 250 V AC
Marking	Bell symbol
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	13.0 mm
Material	ABS (acrylonitrile butadiene-styrene)
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Screws or claws 51...70 mm
Height	83 mm
Width	83 mm
Depth	43.0 mm
Projecting depth	15 mm
Net weight	0.0759 kg

Environment

Standards	IEC 60669-1
Product certifications	VDE
Quality labels	CE
IP degree of protection	IP20
Ambient air temperature for operation	-5...40 °C

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.500 cm
Package 1 Width	8.500 cm
Package 1 Length	8.500 cm
Package 1 Weight	77.000 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.500 cm
Package 2 Width	18.500 cm
Package 2 Length	27.500 cm
Package 2 Weight	834.000 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.000 cm
Package 3 Width	40.000 cm
Package 3 Length	60.000 cm
Package 3 Weight	10.541 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------