



Main

| | |
|----------------------------|--|
| Range | Asfora |
| Product or component type | USB charger |
| Output current | 2.4 A |
| Integrated connection type | 2 USB 2.0 port 5 V DC, maximum load current: 2.4 A |

Complementary

| | |
|--------------------------------|---|
| Device application | Charger |
| Device mounting | Flush |
| Device presentation | Mechanism with fixing frame |
| Colour tint | Steel |
| Surface treatment | Untreated |
| Fixing mode | By claws By screws |
| Type of packing | Flow-pack |
| [Ue] rated operational voltage | 100...240 V AC +/- 10 % at 50/60 Hz |
| Power consumption in W | 0.075 W |
| Nominal output power | 12 W |
| Input power | 12 W |
| Service life in hours | 30000 h 12 W |
| Material | ABS (acrylonitrile butadiene-styrene): centre plate PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover |
| Protection type | Short-circuit protection |
| Number of terminals | 2 screw terminals |
| Clamping connection capacity | 2 x 0.75...2 x 2.5 mm ² for rigid cable(s) 2 x 0.75...2 x 2.5 mm ² for flexible cable(s) 2 x 0.75...2 x 2.5 mm ² for stranded cable(s) |
| Wire stripping length | 8 mm |
| Product compatibility | Mobile/Tablet Mac iOS Mobile/Tablet Android Mobile/tablet Windows |
| Height | 45 mm |
| Width | 22.5 mm |
| Depth | 42 mm |
| Embedding depth | 30.8 mm |

Environment

| | |
|---------------------------------------|---|
| Ambient air temperature for operation | 0...40 °C |
| Ambient air temperature for storage | -5...50 °C |
| Standards | EN 60950-1 EN 62684 ETSI EN 301 489-4 |
| Directives | 2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive |
| Product certifications | EAC |
| Electrical insulation class | Class II |
| IK degree of protection | IK04 |
| IP degree of protection | IP20 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 7.1 cm |
| Package 1 Width | 7.1 cm |
| Package 1 Length | 4.3 cm |
| Package 1 Weight | 81.0 g |
| Unit Type of Package 2 | S02 |
| Number of Units in Package 2 | 24 |
| Package 2 Height | 15.0 cm |
| Package 2 Width | 30.0 cm |
| Package 2 Length | 40.0 cm |
| Package 2 Weight | 1.949 kg |