



Main

Range	Asfora
Product or component type	USB charger
Output current	2.4 A
Integrated connection type	2 USB 2.0 port 5 V DC, maximum load current: 2.4 A

Complementary

Device application	Charger
Device mounting	Flush
Device presentation	Mechanism with fixing frame
Colour tint	Bronze
Surface treatment	Untreated
Fixing mode	By screws By claws
Type of packing	Flow-pack
[Ue] rated operational voltage	100...240 V AC +/- 10 % at 50/60 Hz
Power consumption in W	0.075 W
Nominal output power	12 W
Input power	12 W
Service life in hours	30000 h 12 W
Material	ABS (acrylonitrile butadiene-styrene): centre plate PC (polycarbonate) GF10 FR: casing PC (polycarbonate) GF10 FR: internal cover
Protection type	Short-circuit protection
Number of terminals	2 screw terminals
Clamping connection capacity	2 x 0.75...2 x 2.5 mm ² for rigid cable(s) 2 x 0.75...2 x 2.5 mm ² for flexible cable(s) 2 x 0.75...2 x 2.5 mm ² for stranded cable(s)
Wire stripping length	8 mm
Product compatibility	Mobile/Tablet Mac iOS Mobile/Tablet Android Mobile/tablet Windows
Height	45 mm
Width	22.5 mm
Depth	42 mm
Embedding depth	30.8 mm

Environment

Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-5...50 °C
Standards	EN 60950-1 ETSI EN 301 489-4 EN 62684
Directives	2004/108/EC - electromagnetic compatibility 2006/95/EC - low voltage directive
Product certifications	EAC
Electrical insulation class	Class II
IK degree of protection	IK04
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	7.1 cm
Package 1 Length	4.3 cm
Package 1 Weight	81.0 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	1.949 kg