



### Main

|                               |                             |
|-------------------------------|-----------------------------|
| Range                         | Asfora                      |
| Product or component type     | Socket-outlet               |
| Outlet standard description   | Side earth                  |
| Outlet poles configuration    | 2P + E                      |
| Device presentation           | Mechanism with fixing frame |
| Socket additional information | Lid                         |
| Colour tint                   | Steel                       |
| Type of packing               | Flow-pack                   |

### Complementary

|                         |   |
|-------------------------|---|
| Socket number           | 1   |
| Device mounting         | Flush   |
| Power range             | 3680 W  |
| Rated current           | 16 A at 250 V AC  |
| Connections - terminals | Lift terminals  |
| Number of cables        | 2 cable(s) 2.5 mm <sup>2</sup>  |
| Cable stiffness         | Flexible<br>Rigid<br>Solid stranded                                   |
| Wire stripping length   | 13.0 mm   |
| Material                | ABS + PC: central plate<br>ABS (acrylonitrile butadiene-styrene): lid |
| Surface finish          | Painted   |
| Conductor material      | Copper  |
| Fixing mode             | Screws or claws 51...69 mm  |
| Height                  | 71 mm   |
| Width                   | 71 mm   |
| Depth                   | 42 mm   |
| Projecting depth        | 10 mm   |
| Quantity per set        | 1   |
| Net weight              | 0.073 kg  |

### Environment

|                         |             |
|-------------------------|-------------|
| Standards               | IEC 60884-1 |
| Product certifications  | TSE<br>VDE  |
| IP degree of protection | IP20        |

### Packing Units

|                              |        |
|------------------------------|--------|
| Unit Type of Package 1       | PCE    |
| Number of Units in Package 1 | 1      |
| Package 1 Height             | 4.5 cm |
| Package 1 Width              | 7.0 cm |
| Package 1 Length             | 7.0 cm |

|                              |           |
|------------------------------|-----------|
| Package 1 Weight             | 73.75 g   |
| Unit Type of Package 2       | BB1       |
| Number of Units in Package 2 | 10        |
| Package 2 Height             | 9.5 cm    |
| Package 2 Width              | 18.5 cm   |
| Package 2 Length             | 27.5 cm   |
| Package 2 Weight             | 817.0 g   |
| Unit Type of Package 3       | S04       |
| Number of Units in Package 3 | 120       |
| Package 3 Height             | 30.0 cm   |
| Package 3 Width              | 40.0 cm   |
| Package 3 Length             | 60.0 cm   |
| Package 3 Weight             | 10.369 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| REACH free of SVHC         | Yes   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Toxic heavy metal free     | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |