



Main

Range	Asfora
Product or component type	TV/SAT socket
Device presentation	Mechanism with fixing frame
TV socket type	Intermediate socket (passage)
Wiring device additional information	For series distribution systems
Colour tint	Steel
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Socket number	2
TV connector	Male IEC 9.52 mm
SAT connector	F type
Attenuation	8 dB
DC current flow	In SAT socket
Number per line	4
Connections - terminals	Screwless terminals
Material	ABS (acrylonitrile butadiene-styrene): central plate
Surface finish	Painted
Conductor material	Copper
Fixing mode	Claws51...80 mm
Height	71 mm
Width	71 mm
Depth	42 mm
Projecting depth	13 mm
Net weight	0.105 kg




Environment

Quality labels	CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.4 cm
Package 1 Width	6.3 cm
Package 1 Length	7.0 cm
Package 1 Weight	103.8 g

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins