EPH3500223

Asfora, TV-R-SAT intermediate socket, 4dB, cream



Main	
Range	Asfora
Product or component type	TV/SAT/R socket
Device presentation	Complete product
TV socket type	Intermediate socket (passage)
Wiring device additional information	For series distribution systems
Colour tint	Cream
Type of packing	Flow-pack

$c_{\alpha m}$	alama	ntoni
COIII	oleme	:iiiaiy

TV connector Radio connector Female IEC 9.52 mm SAT connector F type Attenuation 4 dB DC current flow In SAT socket Number per line 4 Connections - terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth Projecting depth 13 mm	Device mounting	Flush	
Radio connector Female IEC 9.52 mm SAT connector F type Attenuation 4 dB DC current flow In SAT socket Number per line 4 Connections - terminals Screwless terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Socket number	3	
SAT connector Attenuation 4 dB DC current flow In SAT socket Number per line 4 Connections - terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	TV connector	Male IEC 9.52 mm	
Attenuation 4 dB DC current flow In SAT socket Number per line 4 Connections - terminals Screwless terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Radio connector	Female IEC 9.52 mm	
DC current flow Number per line 4 Connections - terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth In SAT socket ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Claws5180 mm 43 mm	SAT connector	F type	
Number per line Connections - terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth Projecting depth 13 mm	Attenuation	4 dB	
Connections - terminals Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	DC current flow	In SAT socket	
Material ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Glossy Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Number per line	4	
ABS (acrylonitrile butadiene-styrene): cover frame Surface finish Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Connections - terminals	Screwless terminals	
Conductor material Copper Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Material		
Fixing mode Claws5180 mm Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Surface finish	Glossy	
Height 83 mm Width 83 mm Depth 42 mm Projecting depth 13 mm	Conductor material	Copper	
Width 83 mm Depth 42 mm Projecting depth 13 mm	Fixing mode	Claws5180 mm	
Depth 42 mm Projecting depth 13 mm	Height	83 mm	
Projecting depth 13 mm	Width	83 mm	
, , ,	Depth	42 mm	
Net weight 0.117 kg	Projecting depth	13 mm	
	Net weight	0.117 kg	

Environment

Quality labels	CE
IP degree of protection	IP20

Packing Units

PCE	
1	
11.000 cm	
16.000 cm	
5.000 cm	
120.000 g	
BB1	
10	
9.400 cm	
	1 11.000 cm 16.000 cm 5.000 cm 120.000 g BB1 10

Package 2 Width	18.500 cm
Package 2 Length	27.500 cm
Package 2 Weight	1339.000 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.000 cm
Package 3 Width	30.000 cm
Package 3 Length	40.000 cm
Package 3 Weight	8409.000 kg

Offer Sustainability

REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
₫Yes
China RoHS Declaration
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months