



Main

Range	Asfora
Product or component type	TV/SAT/R socket
Device presentation	Complete product
TV socket type	Intermediate socket (passage)
Wiring device additional information	For series distribution systems
Colour tint	Cream
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Socket number	3
TV connector	Male IEC 9.52 mm
Radio connector	Female IEC 9.52 mm
SAT connector	F type
Attenuation	8 dB
DC current flow	In SAT socket
Number per line	4
Connections - terminals	Screwless terminals
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws51...80 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	13 mm
Net weight	0.117 kg

Environment

Quality labels	CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.0 cm
Package 1 Width	16.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	120.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	9.1 cm

Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	1.339 kg
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	8.409 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------