



Main

Range	Asfora
Product or component type	SAT socket
Device presentation	Complete product
TV socket type	Intermediate socket (passage)
Wiring device additional information	For series distribution systems
Colour tint	White
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Socket number	1
SAT connector	F type
Attenuation	4 dB
DC current flow	In SAT socket
Number per line	4
Connections - terminals	Screwless terminals
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): cover frame
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws51...80 mm
Height	83 mm
Width	83 mm
Depth	42 mm
Projecting depth	13 mm
Net weight	0.087 kg

Environment

Quality labels	CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.0 cm
Package 1 Length	8.0 cm
Package 1 Weight	84.0 g
Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	9.5 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm

Package 2 Weight	921.0 g
Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	40.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	11.686 kg

Offer Sustainability

REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------