



Main

Range	Asfora
Product or component type	SAT socket
Device presentation	Mechanism with fixing frame
TV socket type	Intermediate socket (passage)
Wiring device additional information	For series distribution systems
Colour tint	Aluminium
Type of packing	Flow-pack

Complementary

Device mounting	Flush
Socket number	1
SAT connector	F type
Attenuation	4 dB
DC current flow	In SAT socket
Number per line	4
Connections - terminals	Screwless terminals
Material	ABS (acrylonitrile butadiene-styrene): central plate
Surface finish	Painted
Conductor material	Copper
Fixing mode	Claws 51... 80 mm
Height	71 mm
Width	71 mm
Depth	42 mm
Projecting depth	13 mm
Net weight	0.075 kg

Environment




Quality labels	CE
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.0 cm
Package 1 Width	11.0 cm
Package 1 Length	5.0 cm
Package 1 Weight	78.0 g
Unit Type of Package 2	CAR
Number of Units in Package 2	10
Package 2 Height	9.1 cm
Package 2 Width	18.5 cm
Package 2 Length	27.5 cm
Package 2 Weight	1.039 kg

Unit Type of Package 3	S04
Number of Units in Package 3	120
Package 3 Height	30 cm
Package 3 Width	40 cm
Package 3 Length	60 cm
Package 3 Weight	13.219 kg

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	 Yes
China RoHS Regulation	 China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins