



Main

| | |
|--------------------------------------|---------------------------------|
| Range | Asfora |
| Product or component type | SAT socket |
| Device presentation | Mechanism with fixing frame |
| TV socket type | Intermediate socket (passage) |
| Wiring device additional information | For series distribution systems |
| Colour tint | Steel |
| Type of packing | Flow-pack |

Complementary

| | |
|-------------------------|--|
| Device mounting | Flush |
| Socket number | 1 |
| SAT connector | F type |
| Attenuation | 4 dB |
| DC current flow | In SAT socket |
| Number per line | 4 |
| Connections - terminals | Screwless terminals |
| Material | ABS (acrylonitrile butadiene-styrene): central plate |
| Surface finish | Painted |
| Conductor material | Copper |
| Fixing mode | Claws 51...80 mm |
| Height | 71 mm |
| Width | 71 mm |
| Depth | 42 mm |
| Projecting depth | 13 mm |
| Net weight | 0.075 kg |

Environment




| | |
|-------------------------|------|
| Quality labels | CE |
| IP degree of protection | IP20 |

Packing Units

| | |
|------------------------------|----------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 16.0 cm |
| Package 1 Width | 11.0 cm |
| Package 1 Length | 5.0 cm |
| Package 1 Weight | 78.0 g |
| Unit Type of Package 2 | CAR |
| Number of Units in Package 2 | 10 |
| Package 2 Height | 9.1 cm |
| Package 2 Width | 18.5 cm |
| Package 2 Length | 27.5 cm |
| Package 2 Weight | 1.039 kg |

| | |
|------------------------------|-----------|
| Unit Type of Package 3 | S04 |
| Number of Units in Package 3 | 120 |
| Package 3 Height | 30 cm |
| Package 3 Width | 40 cm |
| Package 3 Length | 60 cm |
| Package 3 Weight | 13.219 kg |

Offer Sustainability

| | |
|----------------------------|---|
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| China RoHS Regulation |  China RoHS Declaration |