



Main

Range	Asfora
Product or component type	Dimmer
Device presentation	Mechanism with fixing frame
Load type	230 V AC halogen lamp: 40...600 W 230 V AC incandescent lamp: 40...600 W Low voltage halogen lamp with ferromagnetic transformer: 40...600 W
Colour tint	Steel
Type of packing	Box

Complementary

Device mounting	Flush
Switch function	1-pole 2-way
Dimmer control	Rotary push type
Dimmer application	Inductive load Ohmic load
Protection type	Fuse protection
Associated fuse rating	6.3 A
[Ue] rated operational voltage	230 V AC 50 Hz
Connections - terminals	Pillar terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Flexible Rigid
Wire stripping length	8 mm
Material	ABS (acrylonitrile butadiene-styrene): central plate ABS (acrylonitrile butadiene-styrene): knob
Surface finish	Painted
Conductor material	Copper
Fixing mode	Claws53...78 mm
Height	71 mm
Width	71 mm
Depth	50 mm
Projecting depth	21 mm
Net weight	0.099 kg

Environment

Product certifications	SEMKO UKR TSE NEMKO GOST VDE FIMKO
Quality labels	CE NF
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.2 cm
Package 1 Width	7.1 cm
Package 1 Length	12.6 cm
Package 1 Weight	102 g
Unit Type of Package 2	S02
Number of Units in Package 2	24
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	2831 kg
Unit Type of Package 3	P12
Number of Units in Package 3	1536
Package 3 Height	128 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	181.18 kg

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins