



### Main

|                           |   |
|---------------------------|---|
| Range                     | Asfora  |
| Product or component type | Dimmer  |
| Device presentation       | Complete product  |
| Load type                 | 230 V AC halogen lamp: 20...315 W<br>230 V AC incandescent lamp: 20...315 W<br>Low voltage halogen lamp with electronic transformer: 20...315 W |
| Colour tint               | White   |
| Type of packing           | Box   |

### Complementary

|                                |   |
|--------------------------------|---|
| Device mounting                | Flush   |
| Switch function                | 1-pole 2-way  |
| Dimmer control                 | Rotary push type  |
| Dimmer application             | Capacitive load<br>Ohmic load   |
| Protection type                | Short-circuit and overload protection with automatic reset  |
| [Ue] rated operational voltage | 230 V AC 50 Hz  |
| Connections - terminals        | Pillar terminals  |
| Number of cables               | 2 cable(s) 2.5 mm <sup>2</sup>  |
| Cable stiffness                | Flexible<br>Rigid   |
| Wire stripping length          | 8 mm  |
| Material                       | ABS (acrylonitrile butadiene-styrene): central plate<br>ABS (acrylonitrile butadiene-styrene): cover frame<br>ABS (acrylonitrile butadiene-styrene): knob |
| Surface finish                 | Glossy  |
| Conductor material             | Copper  |
| Fixing mode                    | Claws53...78 mm   |
| Height                         | 83 mm   |
| Width                          | 83 mm   |
| Depth                          | 49 mm   |
| Projecting depth               | 20 mm   |
| Net weight                     | 0.111 kg  |

### Environment

|                         |  |
|-------------------------|--|
| Product certifications  | VDE<br>GOST<br>SEMKO<br>TSE<br>NEMKO<br>FIMKO<br>UKR |
| Quality labels          | CE   |
| IP degree of protection | IP20   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Packing Units

|                              |          |
|------------------------------|----------|
| Unit Type of Package 1       | PCE      |
| Number of Units in Package 1 | 1        |
| Package 1 Height             | 6.5 cm   |
| Package 1 Width              | 8.5 cm   |
| Package 1 Length             | 8.5 cm   |
| Package 1 Weight             | 153.75 g |
| Unit Type of Package 2       | S02      |
| Number of Units in Package 2 | 24       |
| Package 2 Height             | 15.0 cm  |
| Package 2 Width              | 30.0 cm  |
| Package 2 Length             | 40.0 cm  |
| Package 2 Weight             | 3.928 kg |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|