



Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2 x 2P + E
Device presentation	Complete product
Colour tint	White
Type of packing	Flow-pack

Complementary

Socket number	2
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm ²
Cable stiffness	Solid stranded Rigid Flexible
Wire stripping length	11 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ASA + PC: central plate
Surface finish	Glossy
Conductor material	Copper
Fixing mode	Claws54...72 mm
Height	123 mm
Width	83 mm
Depth	46 mm
Projecting depth	23 mm
Quantity per set	1

Environment

Standards	IEC 60884-1
Product certifications	VDE UKR
IP degree of protection	IP20

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5 cm
Package 1 Width	8.2 cm
Package 1 Length	12.5 cm
Package 1 Weight	102.33 g

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	10 cm
Package 2 Width	20 cm
Package 2 Length	31.5 cm
Package 2 Weight	1.127 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	22 cm
Package 3 Width	32 cm
Package 3 Length	53.5 cm
Package 3 Weight	6.006 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------