# EPH9900161

## Asfora - double socket-outlet with side earth contact, aluminium





Main	
Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2 x 2P + E
Device presentation	Complete product
Colour tint	Aluminium
Type of packing	Flow-pack

Com		

Socket number	2	
Device mounting	Flush	
Power range	3680 W	
Rated current	16 A at 250 V AC	
Connections - terminals	Lift terminals	
Number of cables	2 cable(s) 2.5 mm²	
Cable stiffness	Solid stranded Rigid Flexible	
Wire stripping length	11 mm	
Material	ABS (acrylonitrile butadiene-styrene): cover frame ASA + PC: central plate	
Surface finish	Painted	
Conductor material	Copper	
Fixing mode	Claws5472 mm	
Height	123 mm	
Width	83 mm	
Depth	46 mm	
Projecting depth	23 mm	
Quantity per set	1	

#### Environment

Standards	IEC 60884-1	
Product certifications	VDE AENOR UKR	
IP degree of protection	IP20	

### **Packing Units**

Unit Type of Package 1	PCE	
	4	
Number of Units in Package 1	1	
Package 1 Height	4.5 cm	
Package 1 Width	8.0 cm	
Package 1 Length	12.5 cm	
Package 1 Weight	102.5 g	

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	10.5 cm
Package 2 Width	20.0 cm
Package 2 Length	31.5 cm
Package 2 Weight	1.121 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	21.0 cm
Package 3 Width	32.0 cm
Package 3 Length	53.0 cm
Package 3 Weight	6.001 kg

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation		
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
China RoHS Regulation	☑ China RoHS Declaration	
Environmental Disclosure		