



### Main

Range	Asfora
Product or component type	Socket-outlet
Outlet standard description	Side earth
Outlet poles configuration	2 x 2P + E
Device presentation	Complete product
Colour tint	Steel
Type of packing	Flow-pack

### Complementary

Socket number	2
Device mounting	Flush
Power range	3680 W
Rated current	16 A at 250 V AC
Connections - terminals	Lift terminals
Number of cables	2 cable(s) 2.5 mm <sup>2</sup>
Cable stiffness	Flexible Rigid Solid stranded
Wire stripping length	11 mm
Material	ABS (acrylonitrile butadiene-styrene): cover frame ASA + PC: central plate
Surface finish	Painted
Conductor material	Copper
Fixing mode	Claws54...72 mm
Height	123 mm
Width	83 mm
Depth	46 mm
Projecting depth	23 mm
Quantity per set	1

### Environment

Standards	IEC 60884-1
Product certifications	VDE AENOR UKR
IP degree of protection	IP20

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	8.5 cm
Package 1 Length	12.5 cm
Package 1 Weight	102.25 g

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	10 cm
Package 2 Width	20 cm
Package 2 Length	31.5 cm
Package 2 Weight	1.131 kg
Unit Type of Package 3	CAR
Number of Units in Package 3	50
Package 3 Height	53 cm
Package 3 Width	21 cm
Package 3 Length	32 cm
Package 3 Weight	5.997 kg

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>