


START eco Downlight 195mm Round & Square Recessed

START eco Downlight 195 Square 1400lm 840
0053927



Product features

- START eco Downlight is an integrated LED recessed downlight with built-in non dimmable driver; Loop in loop out connector allows for quick installation; 15W; 1400Lm; 93Lm/W; 4000K.



PRODUCT OVERVIEW

Product name	START eco Downlight 195 Square 1400lm 840
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Retail
ETIM Class	EC001744
Warranty	3 years
Fixture luminous flux (lm)	1400
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Glare control	< 28
Photobiological Risk Group	RG0
Total power consumption (W)	15
Electrical protection	Class II
Dimmable	No
LED Flickering Rate	Medium (21% - 40%)
Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK02
Product EAN number	5410288539270

DATA TABLE

General data

Product name	START eco Downlight 195 Square 1400lm 840
Technology	LED
Housing	PC Polycarbonate
Mount	Ceiling recessed mounting
General application	Retail
Operating temperature range (°C)	-20°C - 40°C

START eco Downlight 195mm Round & Square Recessed

START eco Downlight 195 Square 1400lm 840
0053927

Performance ambient temperature Tq (°C)	25
ETIM Class	EC001744
Warranty	3 years

Optical data

Fixture luminous flux (lm)	1400
Luminaire efficacy (lm/W)	93
Colour temperature (K)	4000
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	110
Distribution type	Symmetric
Glare control	< 28
Photobiological Risk Group	RG0

Electrical data

Total power consumption (W)	15
Mains voltage (V)	220-240V
Lamp power factor	0.5
THD (at 230 V, 50 Hz, full load, at 100% dimming level) xx.x %	115.0
Electrical protection	Class II
Control gear required	No
Dimmable	No
Drive current (mA)	156
Inrush Current (A)	12
Inrush Duration (µs)	200
Glow Wire Test (°C)	650
Energy Efficiency Class (A->G) of contained light source	E
Nominal Frequency (Hz)	50/60Hz
LED Flickering Rate	Medium (21% - 40%)
Max. Luminaires per 10A C Breaker	56
Max. Luminaires per 13A C Breaker	73
Max. Luminaires per 16A C Breaker	91
Max. Luminaires per 20A C Breaker	114
Max. Luminaires per 10A B Breaker	33
Max. Luminaires per 13A B Breaker	43
Max. Luminaires per 16A B Breaker	54
Max. Luminaires per 20A B Breaker	68

Lifetime data

Lifespan L70 B50	30000
------------------	-------

Physical data

Housing colour	RAL 9003 - Signal white
IP rating	IP20
IK rating	IK02
Diffuser finish	Opal

START eco Downlight 195mm Round & Square Recessed

START eco Downlight 195 Square 1400lm 840
0053927

Diffuser material	PC Polycarbonate
Nominal Product Length (mm)	215
Nominal Product Width (mm)	215
Nominal Product Height (mm)	34
Cutout Dimensions (W x L in mm or Diameter in mm)	195x195
Weight (kg)	0.2


Packaging

Single packaging type	Carton
Product EAN number	5410288539270
Packaging single length / height (cm)	23.2
Packaging single width (cm)	4.5
Packaging single depth (cm)	23.2
DUN14 (outer)	15410288539277
Units per outer package	10
Packaging outer length / height (cm)	48.0
Packaging outer width (cm)	24.5
Packaging outer depth (cm)	25.0

Safety data

Optimal operating condition (°C)	-20-40
----------------------------------	--------

PHOTOMETRY



Distance [m]	Cone diameter [m]	Beam diameter [m]	Beam diameter [in]	Illuminance [lx]
0.5	1.56	1.55	61.8"	1990
			61.8"	157
			61.2"	159
1.0	3.12	3.10	123.6"	498
			123.6"	39
			123.2"	41
1.5	4.67	4.66	185.4"	221
			185.4"	17
			185.2"	18
2.0	6.23	6.21	247.2"	124
			247.2"	10
			247.2"	10
2.5	7.79	7.76	309.0"	80
			309.0"	6
			309.2"	6
3.0	9.35	9.31	370.8"	55
			370.8"	4
			371.2"	4

Distance [m] Cone diameter [m] Illuminance [lx]
 C0 - C180 (Half beam angle: 114.4°)
 C90 - C270 (Half beam angle: 114.6°)

TECHNICAL DRAWINGS

