

Gizmo Solar Ground Light

GIZMO SOLAR GROUND LIGHT
0054047



Product features

- High quality inground solar light with twin LED lights and external solar panel
- Integrated daylight sensors
- Automatic light management - light up automatically when it gets dark after detecting any motion
- Easy installation - plug and play solution
- High lumen output - 56lm x 2
- Long rated lifetime - 25,000 hours
- ON/OFF switch
- Robust construction - stainless steel and ABS housing
- Perfect for gardens, flower beds, pathways, tree lighting
- Colour temperature - Cool White 4000K
- Operating temperature: -10°C to 40°C



PRODUCT OVERVIEW

Product name	GIZMO SOLAR GROUND LIGHT
Technology	LED
Cap/Base	N/A
Housing	ABS Plastic, Stainless steel
Mount	Ground mounted, Ground recessed
General application	Residential & Consumer
ETIM Class	N/A
Warranty	3 years
Fixture luminous flux (lm)	112
Luminaire efficacy (lm/W)	56
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Photobiological Risk Group	RG1
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Housing colour	Black
IP rating	IP65
IK rating	IK04
Product EAN number	5410288540474
Dimming method	N/A
Light source included	INTEGRATED LED

Gizmo Solar Ground Light

GIZMO SOLAR GROUND LIGHT
0054047

DATA TABLE

General data

Product name	GIZMO SOLAR GROUND LIGHT
Technology	LED
Cap/Base	N/A
Housing	ABS Plastic, Stainless steel
Mount	Ground mounted, Ground recessed
General application	Residential & Consumer
Operating temperature range (°C)	-10°C - 40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	N/A
Warranty	3 years

Optical data

Fixture luminous flux (lm)	112
Luminaire efficacy (lm/W)	56
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Beam Angle (°)	100
Distribution type	Diffuse
Photobiological Risk Group	RG1

Electrical data

Mains voltage (V)	5V
Electrical protection	Class III
Control gear type	LED driver constant current
Dimmable	No
Drive current (mA)	350
Glow Wire Test (°C)	650
Nominal Frequency (Hz)	N/A

Lifetime data

Lifespan L70 B50	30000
------------------	-------

Physical data

Housing colour	Black
IP rating	IP65
IK rating	IK04
Diffuser finish	Diffuse
Diffuser material	Glass
Reflector finish	None
Nominal Product Height (mm)	45
Nominal Product Diameter (mm)	120
Weight (kg)	1.216

Gizmo Solar Ground Light

GIZMO SOLAR GROUND LIGHT
0054047

Packaging

Single packaging type	Carton
Product EAN number	5410288540474
Packaging single length / height (cm)	25.0
Packaging single width (cm)	23.0
Packaging single depth (cm)	8.5
DUN14 (outer)	15410288540471
Units per outer package	6
Packaging outer length / height (cm)	52.3
Packaging outer width (cm)	25.3
Packaging outer depth (cm)	28.3

Safety data

Optimal operating condition (°C)	-10-40
----------------------------------	--------

TECHNICAL DRAWINGS

