

## 94196

OSRAM ORIGINAL LINE | Halogen headlight lamps



### Areas of application

- Headlight

### Product benefits

- OEM Quality
- Wide product range
- Reliable quality

### Product features

- Original spare parts



## Technical data

### Electrical data


Power input	85 / 80 W <sup>1)</sup>
Nominal voltage	24.0 V
Nominal wattage	75/70 W
Test voltage	28.0 V

<sup>1)</sup> Maximum

### Photometrical data

Luminous flux	1900/1200 lm
Luminous flux tolerance	±15 / ±15 %

### Dimensions & weight



Length	82.0 mm
Product weight	25.60 g

### Lifespan

Lifespan B3	170 / 500 h <sup>1)</sup>
Lifespan Tc	400 / 1500 h <sup>1)</sup>

<sup>1)</sup> Filament 1 / Filament 2

### Additional product data

Base (standard designation)	P43t
-----------------------------	------

### Certificates & standards

ECE category	H4
--------------	----

### Country specific categorizations

Product datasheet

Order reference	94196 75/70W 24
-----------------	-----------------

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300250632	OSRA94196	-	-	-

## Product datasheet

---

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300250632	94196	Folding carton box 1	71 mm x 47 mm x 47 mm	0.16 dm <sup>3</sup>	33.60 g
4050300250649	94196	Bundle 10	144 mm x 71 mm x 193 mm	1.97 dm <sup>3</sup>	336.00 g
4050300250656	94196	Shipping carton box 100	485 mm x 160 mm x 250 mm	19.40 dm <sup>3</sup>	3613.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.