
SPOT LED 4 W 3000 K

LEDVANCE SPOT LED ADJUST 68 | Indoor LED spotlights



Areas of application

- Replacement of conventional 50 W halogen spotlights
- General illumination
- Hotel rooms
- Bars, restaurants
- Accent lighting
- Galleries, museums

Product benefits

- Design matches the LEDVANCE DOWNLIGHT luminaire family
- Energy savings of up to 90 % compared to halogen lamp spotlights
- Functional and minimalistic design
- Easy and quick installation
- External driver for extended flexibility (compatible with selected DALI drivers)
- 3 years guarantee

Product features

- Luminous efficacy: 85 lm/W
- Luminous flux: up to 550 lm
- Color temperature: 3,000 K
- Initial color consistency: ≤ 4 SDCM
- Beam angle: 36°
- Compatible with standard ceiling cutouts of 68 mm
- Type of protection: IP20
- Housing material: aluminum



Product datasheet

- Lens material: PMMA
- Lifetime: up to 30,000 h
- Certificates: CE, CB, TUEV SUED

Product datasheet

Technical data

Electrical data

Operating mode	Electronic control gear (EVG)
Nominal wattage	4.50 W
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Nominal current	0.02 A


Photometrical data

Color temperature	3000 K
Luminous flux	360 lm
Luminous intensity	710 cd
Light color (designation)	Warm White
Color rendering index Ra	>80

Light technical data

Beam angle	36 °
------------	------

Dimensions & weight



Diameter	80.0 mm
Height	36.0 mm
Mounting diameter	68 mm

Colors & materials

Body material	Aluminum
Product color	White

Temperatures & operating conditions

Product datasheet

Ambient temperature range	-20...45 °C
---------------------------	-------------

Lifespan

Lifespan	30000 h
----------	---------

Capabilities

Dimmable	No
Type of connection	Terminal, 2-pin

Certificates & standards

Protection class	II
Type of protection	IP20

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075000124	SPOT LED 4 W 3000 K	Shipping carton box 30	575 mm x 230 mm x 225 mm	29.76 dm ³	6808.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.