

PRODUCT DATASHEET SubMARINE Integrated Slim Value 10 W 0.6 m

SubMARINE Integrated Slim Value | Flat and slim dampproof luminaires with integrated LED module

AREAS OF APPLICATION

- Basements, garages, warehouses



PRODUCT BENEFITS

- Easy installation, no tools required for connection
- 3 years guarantee
- Impressive for its low-profile design

PRODUCT FEATURES

- Damp-proof luminaires
- Dust-protected and jet-proof (IP65)
- Extremely low profile
- Not dimmable



TECHNICAL DATA

Electrical data

Nominal wattage	10.00 W
Nominal voltage	220240 V
Mains frequency	50/60 Hz

Photometrical data

Color temperature	4000 К
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	900 lm
Luminous efficacy	90 lm/W

Dimensions & weight



Length	715.0 mm
Width	53.0 mm
Height	35.0 mm
Product weight	194.00 g

Colors & materials

Body material	Polycarbonate (PC)	
Housing color	White	
Product color	White	

Temperatures & operating conditions

Lifespan

Lifespan		30000 h
----------	--	---------

Additional product data

Mounting type	Surface	Surface		
Capabilities				
Dimmable	No			
Type of connection	Terminal, 2-Pole (L, N)			
Certificates & standards				
Protection class	П			
Type of protection	IP65			
Standards	CE/EAC/REACH/RoHS			

EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075140004	SubMARINE Integrated Slim Value 10 W 0.6 m	Shipping carton box 20	750 mm x 249 mm x 225 mm	42.02 dm ³	4809.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

www.osram-lamps.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.