

# PRODUCT DATASHEET

## PANEL 625 36 W 4000 K OP IP54 WT

PANEL 625 IP54 | Square edge-lit panel luminaires and high IP rating, 600 mm



---

### AREAS OF APPLICATION

- Direct replacement for luminaires with fluorescent lamps
- Corridors
- Offices
- Conference rooms
- Reception areas
- Hospitals
- Laboratories
- Suitable for recessed ceiling systems with grid size of 625 x 625 mm

---

### PRODUCT BENEFITS

- Energy savings of up to 50 % (compared to luminaires that use fluorescent lamps)
- External driver for extended flexibility
- Light guide plate with micro structure made of non-yellowing material for long lifetime
- Easy and quick installation
- Low flicker light thanks to special electronic control gear
- 5 years guarantee

---

### PRODUCT FEATURES

- Lifetime (L80/B50): up to 60,000 h (at 25 °C)
- Aluminum housing, PMMA diffuser
- High luminous efficacy: up to 120 lm/W
- Initial color consistency: < 4 SDCM
- Ambient temperature in operation: -10...+40 °C
- Type of protection: IP54



**TECHNICAL DATA**

Electrical data

Nominal wattage	36.00 W
Operating mode	External LED driver
Nominal voltage	220...240 V
Mains frequency	50/60 Hz
Power factor $\lambda$	>0.90

Luminaire control gear data

ECG - Length	150 mm
ECG - Width	41.4 mm



Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	4320 lm
Luminous efficacy	120 lm/W
Standard deviation of color matching	<4 sdc <sub>m</sub>

Light technical data

Beam angle	120 °
------------	-------

Dimensions & weight



Length	620.0 mm
Width	620.0 mm
Height	12.6 mm
Product weight	3200.00 g
Mounting width	600 mm

<b>Mounting length</b>	600 mm
------------------------	--------

### Colors & materials

<b>Housing color</b>	White
<b>Product color</b>	White
<b>Body material</b>	Aluminum
<b>Cover material</b>	Polymethylmethacrylate (PMMA)

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-10...45 °C
----------------------------------	-------------

### Lifespan

<b>Lifespan L70 at 25 °C</b>	70000 h
<b>Lifespan L80 at 25 °C</b>	60000 h
<b>Lifespan L90 at 25 °C</b>	35000 h

### Additional product data

<b>Mounting type</b>	Recessed/Suspended/Surface
<b>Mounting location</b>	Ceiling / Wall



### Capabilities

<b>Dimmable</b>	No
<b>Type of connection</b>	Screw terminal, 2-Pole (L,N)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Type of protection</b>	IP54
<b>Protection class</b>	II
<b>Protection class IK (shock resistance)</b>	IK04
<b>Glow Wire Test according to IEC 695-2-1</b>	650 °C
<b>Photobiological safety group</b>	RG 0
<b>Standards</b>	CE/CB/ENEC/TÜV SÜD/EAC/RoHS

Light Distribution



LDC typ cone

LDC typ polar

EQUIPMENT / ACCESSORIES

- Accessories for several mounting options available
- Security rope for luminaire included
- External control gear included

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075149540	PANEL 625 36 W 4000 K OP IP54 WT	Shipping carton box 4	665 mm x 270 mm x 670 mm	120.30 dm <sup>3</sup>	14950.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For Guarantee see

- ▶ [www.ledvance.com/guarantee](http://www.ledvance.com/guarantee)

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.