

# **PRODUCT DATASHEET**ENDURA PRO FLOOD SENSOR 15 W 1500 840 IP55 DG

ENDURA PRO FLOOD SENSOR | High efficiency wall sensor luminaires with wide beam angle in innovative optical design



#### **AREAS OF APPLICATION**

- Outdoor
- Parking lots, city squares, parks
- Arcade passage

## **PRODUCT BENEFITS**

- Homogenous illumination
- Lighting according to requirements due to adjustable luminaire head
- Easy and quick installation

## **PRODUCT FEATURES**

- 4 operating modes selectable (light 6h continous on, standby, switch-on by movement or dusk)
- Adjustable luminaire head
- Type of protection: IP55
- Impact resistance: IK05
- Protection class: II



# **TECHNICAL DATA**

# Electrical data

Nominal wattage	15.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz


# Photometrical data

Color temperature	4000 K
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	1500 lm
Luminous efficacy	100 lm/W

## Luminaire sensor data

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)
Sensor detection angle	180 °
Detection range of motion sensor	12 m
Detection threshold of daylight sensor	11000 lx
Sensor controlled switching time	2 s15 min

# Dimensions & weight



Length	151.0 mm
Width	56.0 mm
Height	205.0 mm
Product weight	365.00 g

## Colors & materials

Body material	Polycarbonate (PC)
Housing color	Dark gray
Product color	Dark gray
Housing color	Dark gray

# Temperatures & operating conditions

# Additional product data

Mounting type	Surface
Mounting location	Wall

## Capabilities

Dimmable	No
Type of connection	Cable, 2-pole
LED module replaceable	Not replaceable

#### Certificates & standards

Protection class	II
Type of protection	IP55
Standards	CE/EAC/REACH/RoHS

## **LOGISTICAL DATA**

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075228801	Folding carton box 1	68 mm x 158 mm x 214 mm	418.00 g	2.30 dm <sup>3</sup>
4058075228818	Shipping carton box 6	326 mm x 213 mm x 231 mm	2.79 g	16.04 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

# **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.