

PRODUCT DATASHEET ENDURA PRO FLOOD SENSOR 30 W 3000 840 IP55 DG

ENDURA PRO FLOOD SENSOR | High efficiency wall sensor luminaires with wide beam angle in innovative optical design



AREAS OF APPLICATION

- Outdoor
- Parking lots, city squares, parks
- Arcade passage

PRODUCT BENEFITS

- Homogenous illumination
- Lighting according to requirements due to adjustable luminaire head
- Easy and quick installation

PRODUCT FEATURES

- 4 operating modes selectable (light 6h continous on, standby, switch-on by movement or dusk)
- Adjustable luminaire head
- Type of protection: IP55
- Impact resistance: IK05
- Protection class: II



TECHNICAL DATA

Electrical data

Nominal wattage	30.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Mains frequency	50/60 Hz


Photometrical data

Color temperature	4000 К
Color rendering index Ra	≥80
Light color (designation)	Cool White
Luminous flux	1500 lm
Luminous efficacy	50 lm/W

Luminaire sensor data

Type of sensor	Light / Motion	
Sensor technology Passive infrared (PIR)		
Sensor detection angle 180 °		
Detection range of motion sensor	12 m	
Detection threshold of daylight sensor	11000 lx	
Sensor controlled switching time	2 s15 min	

Dimensions & weight



Length	201.0 mm
Width	56.0 mm
Height	225.0 mm
Product weight	480.00 g

Colors & materials

Body material	Polycarbonate (PC)
Housing color	Dark gray
Product color	Dark gray
Housing color	Dark gray

Temperatures & operating conditions

Ambient temperature range	-20+40 °C
---------------------------	-----------

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Cable, 2-pole
LED module replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP55
Standards	CE/EAC/REACH/RoHS

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075228849	Folding carton box 1	68 mm x 208 mm x 234 mm	553.00 g	3.31 dm³
4058075228856	Shipping carton box 4	280 mm x 219 mm x 251 mm	2.49 g	15.39 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.