

PRODUCT DATASHEETLEDstixx

LEDstixx | Little helpers



AREAS OF APPLICATION

- Sideboards
- Flower arrangements
- Practical adhesive surface or drill holes
- Horizontal or vertical alignment on walls or objects

PRODUCT BENEFITS

- Very compact LED luminaire

PRODUCT FEATURES

- Modern luminaire
- High-quality aluminum casing



TECHNICAL DATA


Electrical data

Nominal wattage	0.6 W
Operating mode	Battery
Nominal voltage	4.5 V

Photometrical data

Color temperature	6200 K
Color rendering index Ra	≥80
Luminous flux	25 lm
Luminous efficacy	42 lm/W

Dimensions & weight



Length	222.0 mm
Width	16.2 mm
Height	22.0 mm
Product weight	94.00 g

Colors & materials

Body material	Aluminum
Housing color	Silver
Product color	Silver
Housing color	Silver

Temperatures & operating conditions

Ambient temperature range	-20+60 °C
---------------------------	-----------

Additional product data

Mounting type	Surface
---------------	---------

Mounting location	Wall
Capabilities	
Dimmable	No

Not replaceable

Certificates & standards

LED module replaceable

Protection class	III
Type of protection	IP20
Standards	CE

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227866	Role 1	72 mm x 72 mm x 280 mm	171.00 g	1.45 dm³
4058075227873	Shipping carton box 6	230 mm x 160 mm x 283 mm	1297.00 g	10.41 dm³
4058075227880	Shipping carton box 24	537 mm x 337 mm x 283 mm	6128.00 g	51.21 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.