

# PRODUCT DATASHEET

## CABINET LED Corner 350 two light

Cabinet LED Corner | Low voltage undercabinet luminaires for corner application

---

### AREAS OF APPLICATION

- Shelf and undercabinet lighting



---

### PRODUCT BENEFITS

- Low voltage luminaire for DC operation with external driver
- Suitable for mounting in corners
- Homogenous light distribution
- Easy and fast mounting on nearly every surface (adhesive tape or screws)

---

### PRODUCT FEATURES

- Luminous flux: up to 480 lm
- Switch on and off by movements with 5 cm distance in front of the infrared motion sensor
- Stepless dimming by covering the infrared motion sensor in 5 cm distance for at least one second
- Material: aluminum
- Color: silver
- Available in two lengths: 35 cm and 55 cm
- Available as single and double luminaire kit



## TECHNICAL DATA

### Electrical data

<b>Nominal wattage</b>	9.00 W
<b>Operating mode</b>	External LED driver
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

### Photometrical data

<b>Color temperature</b>	3000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Warm White
<b>Luminous flux</b>	640 lm
<b>Luminous efficacy</b>	71 lm/W

### Luminaire sensor data

<b>Sensor technology</b>	Infrared/Photocell
<b>Detection range of motion sensor</b>	5 cm

### Dimensions & weight



<b>Length</b>	350.0 mm
<b>Width</b>	40.7 mm
<b>Height</b>	23.0 mm
<b>Product weight</b>	423.00 g
<b>Cable length</b>	1500 mm

### Colors & materials

<b>Body material</b>	Polycarbon/Acrylonitrile
<b>Product color</b>	Gray
<b>Housing color</b>	Gray

<b>Cover material</b>	Polycarbonate (PC)
-----------------------	--------------------

### Temperatures & operating conditions

<b>Ambient temperature range</b>	-20...+40 °C
<b>Temperature range in operation</b>	-20...+40 °C

### Lifespan

<b>Number of switching cycles</b>	100000
<b>Rated lamp life time</b>	30000 h

### Additional product data

<b>Mounting type</b>	Surface
<b>Mounting location</b>	Cabinet undersides
<b>Mercury content</b>	0.0 mg

### Capabilities

<b>Dimmable</b>	Yes
<b>Type of connection</b>	Plug type C (EU)
<b>LED module replaceable</b>	Not replaceable

### Certificates & standards

<b>Protection class</b>	II
<b>Type of protection</b>	IP20
<b>Standards</b>	CE/RoHS/EAC
<b>ErP For end-consumer</b>	yes
<b>EEL of included LED module</b>	A++/A+/A

### Logistical data

<b>ErP For end-consumer</b>	yes
-----------------------------	-----

## EQUIPMENT / ACCESSORIES

- External mains adapter (cable length: 1.5 m) included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075227910	Folding carton box 1	94 mm x 71 mm x 400 mm	493.00 g	2.67 dm <sup>3</sup>
4058075227927	Shipping carton box 8	416 mm x 303 mm x 205 mm	4317.00 g	25.84 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

**DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.