

PRODUCT DATASHEET

DoorLED Down White

Door LED Down | Mobile luminaire for entrance areas, light outlet down



AREAS OF APPLICATION

- For a very large range of uses
- Indoor and outdoor
- Entrance lighting
- Corridors
- Patios, balconies

PRODUCT BENEFITS

- Attractive and functional design
- Economical operation due to low power consumption
- Easy and quick installation
- Accessories for flexible mounting options included

PRODUCT FEATURES

- Integrated light and motion sensor
- Available in two housing colors
- Type of protection: IP54



TECHNICAL DATA

Electrical data

Nominal wattage	0.95 W
Operating mode	Battery
Nominal voltage	4.5 V
Mains frequency	0 Hz


Photometrical data

Color temperature	4000 K
Color rendering index Ra	>80
Light color (designation)	Cool White
Luminous flux	40 lm
Luminous efficacy	42 lm/W

Luminaire sensor data

Type of sensor	Light / Motion
Sensor technology	Passive infrared (PIR)

Dimensions & weight



Length	102.5 mm
Width	92.4 mm
Height	36.5 mm
Product weight	154.00 g

Colors & materials

Body material	Polycarbonate (PC)
Housing color	White
Product color	White
Housing color	White

Temperatures & operating conditions

Ambient temperature range	-10...+40 °C
----------------------------------	--------------

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
LED module replaceable	Not replaceable

Certificates & standards

Protection class	III
Type of protection	IP54
Standards	CE/EAC/REACH/RoHS

EQUIPMENT / ACCESSORIES

– Batteries included: 4x 1.5 V LR6 (AA)

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075267848	Blister 1	39 mm x 140 mm x 195 mm	178.00 g	1.06 dm ³
4058075267855	Shipping carton box 6	247 mm x 154 mm x 210 mm	1202.00 g	7.99 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.